

SAFETY DATA SHEET



Ti-Pure™ R-350 Titanium Dioxide Pigment

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 2023/04/11 |
| 4.3 | 2023/12/11 | 1583657-00017 | Date of first issue: 2017/04/21 |

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Ti-Pure™ R-350 Titanium Dioxide Pigment

SDS-Identcode : 130000030909

Other means of identification : None

Recommended use of the chemical and restrictions on use

Recommended use : Colouring agent
Pigment

Restrictions on use : For industrial use only.

Manufacturer or supplier's details

Company : The Chemours (Taiwan) Company Limited

Address : 14th Floor, Hung Kuo Building, 167 Tun Hwa North Road, Taipei, Taiwan

Telephone : 0080-112-7758

Emergency telephone number : 0800 055 119 (in case of chemical spill, fire or poisoning accident)

Telefax : 02-2719-8516

2. HAZARDS IDENTIFICATION

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

SAFETY DATA SHEET



Ti-Pure™ R-350 Titanium Dioxide Pigment

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 2023/04/11 |
| 4.3 | 2023/12/11 | 1583657-00017 | Date of first issue: 2017/04/21 |

| Hazardous ingredients | CAS-No. | Concentration (% w/w) |
|-----------------------------|------------|-----------------------|
| Titanium dioxide | 13463-67-7 | >= 90 -<= 100 |
| Silicon dioxide, amorphous# | 7631-86-9 | >= 1 -< 10 |
| Aluminium hydroxide# | 21645-51-2 | >= 0.1 -< 1 |

Voluntarily-disclosed substance

4. FIRST AID MEASURES

First aid measures for different exposure routes

- | | |
|---|---|
| If inhaled | : If inhaled, remove to fresh air. Get medical attention if symptoms occur. |
| In case of skin contact | : Wash with water and soap as a precaution. Get medical attention if symptoms occur. |
| In case of eye contact | : Flush eyes with water as a precaution. Get medical attention if irritation develops and persists. |
| If swallowed | : If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water. |
| Most important symptoms and effects, both acute and delayed | : irritant effects |
| Protection of first-aiders | : No special precautions are necessary for first aid responders. |
| Notes to physician | : Treat symptomatically and supportively. |

5. FIREFIGHTING MEASURES

- | | |
|---------------------------------------|---|
| Suitable extinguishing media | : Not applicable Will not burn |
| Unsuitable extinguishing media | : Not applicable Will not burn |
| Specific hazards during fire-fighting | : Exposure to combustion products may be a hazard to health. |
| Hazardous combustion products | : No hazardous combustion products are known |
| Specific extinguishing methods | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area. |

SAFETY DATA SHEET



Ti-Pure™ R-350 Titanium Dioxide Pigment

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 4.3 | 2023/12/11 | 1583657-00017 | 2023/04/11 |
| | | | Date of first issue: 2017/04/21 |

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.
Use personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

7. HANDLING AND STORAGE

Handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment.

Storage

Conditions for safe storage : Keep in properly labelled containers.
Store in accordance with the particular national regulations.

Materials to avoid : No special restrictions on storage with other products.

SAFETY DATA SHEET



Ti-Pure™ R-350 Titanium Dioxide Pigment

Version 4.3 Revision Date: 2023/12/11 SDS Number: 1583657-00017 Date of last issue: 2023/04/11
Date of first issue: 2017/04/21

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|---------------------|------------|-------------------------------------|--|--------|
| Titanium dioxide | 13463-67-7 | TWA | 10 mg/m ³ | TW OEL |
| | | STEL | 15 mg/m ³ | TW OEL |
| | | TWA (Respirable particulate matter) | 2.5 mg/m ³ (Titanium dioxide) | ACGIH |
| Aluminium hydroxide | 21645-51-2 | TWA (Respirable particulate matter) | 1 mg/m ³ (Aluminium) | ACGIH |

Biological occupational exposure limits

Contains no substances with biological exposure indices.

Engineering measures : Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Particulates type

Hand protection

Remarks : Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety glasses

Skin and body protection : Skin should be washed after contact.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : crystalline

SAFETY DATA SHEET



Ti-Pure™ R-350 Titanium Dioxide Pigment

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 2023/04/11 |
| 4.3 | 2023/12/11 | 1583657-00017 | Date of first issue: 2017/04/21 |

| | | |
|--|---|---|
| Colour | : | white |
| Odour | : | odourless |
| Odour Threshold | : | No data available |
| pH | : | No data available |
| Melting point/freezing point | : | 1,843 °C |
| Initial boiling point and boiling range | : | 3,000 °C |
| Flash point | : | Not applicable |
| Evaporation rate | : | Not applicable |
| Flammability (solid, gas) | : | Will not burn |
| | | Not expected to form explosive dust-air mixtures. |
| Upper explosion limit / Upper flammability limit | : | No data available |
| Lower explosion limit / Lower flammability limit | : | No data available |
| Vapour pressure | : | Not applicable |
| Relative vapour density | : | Not applicable |
| Relative density | : | 3.6 - 4.3 |
| Solubility(ies) | | |
| Water solubility | : | insoluble |
| Partition coefficient: n-octanol/water | : | Not applicable |
| Auto-ignition temperature | : | No data available |
| Decomposition temperature | : | The substance or mixture is not classified self-reactive. |
| Viscosity | | |
| Viscosity, kinematic | : | Not applicable |
| Explosive properties | : | Not explosive |

SAFETY DATA SHEET



Ti-Pure™ R-350 Titanium Dioxide Pigment

| | | | |
|----------------|------------------------------|------------------------------|---|
| Version 4.3 | Revision Date: 2023/12/11 | SDS Number: 1583657-00017 | Date of last issue: 2023/04/11 Date of first issue: 2017/04/21 |
|----------------|------------------------------|------------------------------|---|

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : No data available

10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : None known.

Conditions to avoid : None known.

Incompatible materials : None.

Hazardous decomposition products : No hazardous decomposition products are known.

11. TOXICOLOGICAL INFORMATION

Exposure routes : Skin contact
Ingestion
Eye contact

Symptoms of Overexposure : irritant effects

Acute toxicity

Not classified based on available information.

Components:

Titanium dioxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 425

Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : Acute toxicity estimate (Rat): > 2,000 mg/kg
Method: Expert judgement
Assessment: The substance or mixture has no acute dermal toxicity

SAFETY DATA SHEET



Ti-Pure™ R-350 Titanium Dioxide Pigment

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 2023/04/11 |
| 4.3 | 2023/12/11 | 1583657-00017 | Date of first issue: 2017/04/21 |

Silicon dioxide, amorphous:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 2.08 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Aluminium hydroxide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 423
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 5.09 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Components:

Titanium dioxide:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Silicon dioxide, amorphous:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Aluminium hydroxide:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

SAFETY DATA SHEET



Ti-Pure™ R-350 Titanium Dioxide Pigment

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 2023/04/11 |
| 4.3 | 2023/12/11 | 1583657-00017 | Date of first issue: 2017/04/21 |

Components:

Titanium dioxide:

| | | |
|---------|---|-------------------------|
| Species | : | Rabbit |
| Result | : | No eye irritation |
| Method | : | OECD Test Guideline 405 |

Silicon dioxide, amorphous:

| | | |
|---------|---|-------------------------|
| Species | : | Rabbit |
| Result | : | No eye irritation |
| Method | : | OECD Test Guideline 405 |

Aluminium hydroxide:

| | | |
|---------|---|-------------------------|
| Species | : | Rabbit |
| Result | : | No eye irritation |
| Method | : | OECD Test Guideline 405 |

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Titanium dioxide:

| | | |
|-----------------|---|-------------------------|
| Test Type | : | Buehler Test |
| Exposure routes | : | Skin contact |
| Species | : | Guinea pig |
| Method | : | OECD Test Guideline 406 |
| Result | : | negative |

| | | |
|-----------------|---|-------------------------------|
| Test Type | : | Local lymph node assay (LLNA) |
| Exposure routes | : | Skin contact |
| Species | : | Mouse |
| Method | : | OECD Test Guideline 429 |
| Result | : | negative |

| | | |
|-----------------|---|------------|
| Exposure routes | : | Inhalation |
| Species | : | Mouse |
| Result | : | negative |

| | | |
|-----------------|---|------------|
| Exposure routes | : | Inhalation |
| Species | : | Humans |
| Result | : | negative |

Aluminium hydroxide:

| | | |
|-----------|---|-------------------|
| Test Type | : | Maximisation Test |
|-----------|---|-------------------|

Ti-Pure™ R-350 Titanium Dioxide Pigment

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 2023/04/11 |
| 4.3 | 2023/12/11 | 1583657-00017 | Date of first issue: 2017/04/21 |

| | |
|-----------------|---------------------------|
| Exposure routes | : Skin contact |
| Species | : Guinea pig |
| Method | : OECD Test Guideline 406 |
| Result | : negative |

Chronic toxicity**Germ cell mutagenicity**

Not classified based on available information.

Components:**Titanium dioxide:**

| | |
|-----------------------|---|
| Genotoxicity in vitro | : Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative |
|-----------------------|---|

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

Test Type: comet assay
Method: OPPTS 870.5140
Result: positive

| | |
|----------------------|--|
| Genotoxicity in vivo | : Test Type: In vivo mammalian alkaline comet assay Species: Rat Application Route: intratracheal Method: OECD Test Guideline 489 Result: negative |
|----------------------|--|

Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative

Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Mouse
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 475
Result: negative

Test Type: Transgenic rodent germ cell gene mutation assay
Species: Mouse
Application Route: Intravenous injection

SAFETY DATA SHEET



Ti-Pure™ R-350 Titanium Dioxide Pigment

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 4.3 | 2023/12/11 | 1583657-00017 | 2023/04/11 |
| | | | Date of first issue: 2017/04/21 |

Method: OECD Test Guideline 488

Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Silicon dioxide, amorphous:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: Ingestion
Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Aluminium hydroxide:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro

Result: positive

Remarks: Based on data from similar materials

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)

Result: equivocal

Remarks: Based on data from similar materials

Test Type: in vitro micronucleus test

Result: positive

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative

Carcinogenicity

Not classified based on available information.

Product:

Remarks : In lifetime inhalation studies rats were exposed for 2 years to

Ti-Pure™ R-350 Titanium Dioxide Pigment

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 4.3 | 2023/12/11 | 1583657-00017 | 2023/04/11 |
| | | | Date of first issue: 2017/04/21 |

respectively 10, 50 and 250 mg/m³ of respirable TiO₂. Slight lung fibrosis was observed at 50 and 250 mg/m³ levels. Microscopic lung tumours were also observed in 13 percent of the rats exposed to 250 mg/m³, an exposure level that caused lung overloading and impairment of rat lungs clearance mechanisms.

In further studies, these tumours were found to occur only under particle overload conditions in a uniquely sensitive species, the rat, and have little or no relevance for humans. The pulmonary inflammatory response to TiO₂ particles exposure was also found to be much more severe in rats than in other rodent species.

In February 2006, IARC has re-evaluated Titanium dioxide as pertaining to Group 2B: "possibly carcinogenic to humans", based upon inadequate evidence in humans and sufficient evidence in experimental animals for the carcinogenicity of titanium dioxide. IARC evaluation guidelines consider the generation of tumours, in 2 different studies within the same animal species, to be adequate criteria for an assessment of sufficient evidence.

The conclusions of several epidemiology studies on more than 20000 TiO₂ industry workers in Europe and the USA did not suggest a carcinogenic effect of TiO₂ dust on the human lung. Mortality from other chronic diseases, including other respiratory diseases, was also not associated with exposure to TiO₂ dust.

Based upon all available study results, Chemours scientists conclude that titanium dioxide will not cause lung cancer or chronic respiratory diseases in humans at concentrations experienced in the workplace.

Components:**Titanium dioxide:**

| | | |
|-------------------|---|-----------------------------|
| Species | : | Rat |
| Application Route | : | inhalation (dust/mist/fume) |
| Exposure time | : | 2 Years |
| Result | : | negative |

| | | |
|-------------------|---|-----------|
| Species | : | Rat |
| Application Route | : | Ingestion |
| Exposure time | : | 105 weeks |
| Result | : | negative |

| | | |
|-------------------|---|-----------|
| Species | : | Mouse |
| Application Route | : | Ingestion |
| Exposure time | : | 103 weeks |
| Result | : | negative |

| | | |
|------------------------------|---|--|
| Carcinogenicity - Assessment | : | Weight of evidence does not support classification as a carcinogen |
|------------------------------|---|--|

SAFETY DATA SHEET



Ti-Pure™ R-350 Titanium Dioxide Pigment

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 2023/04/11 |
| 4.3 | 2023/12/11 | 1583657-00017 | Date of first issue: 2017/04/21 |

Silicon dioxide, amorphous:

| | |
|-------------------|-------------|
| Species | : Rat |
| Application Route | : Ingestion |
| Exposure time | : 103 weeks |
| Result | : negative |

| | |
|------------------------------|--|
| Carcinogenicity - Assessment | : Weight of evidence does not support classification as a carcinogen |
|------------------------------|--|

Aluminium hydroxide:

| | |
|-------------------|--|
| Species | : Rat |
| Application Route | : inhalation (dust/mist/fume) |
| Exposure time | : 86 weeks |
| Result | : negative |
| Remarks | : Based on data from similar materials |

Reproductive toxicity

Not classified based on available information.

Components:

Titanium dioxide:

| | |
|----------------------|--|
| Effects on fertility | : Test Type: One-generation reproduction toxicity study Species: Rat Application Route: Ingestion Method: OECD Test Guideline 443 Result: negative |
|----------------------|--|

| | |
|-------------------------------|--|
| Effects on foetal development | : Test Type: Prenatal development toxicity study (teratogenicity) Species: Rat Application Route: Ingestion Method: OECD Test Guideline 414 Result: negative |
|-------------------------------|--|

| | |
|------------------------------------|--|
| Reproductive toxicity - Assessment | : Weight of evidence does not support classification for reproductive toxicity |
|------------------------------------|--|

Silicon dioxide, amorphous:

| | |
|-------------------------------|--|
| Effects on foetal development | : Test Type: Embryo-foetal development Species: Rat Application Route: Ingestion Result: negative |
|-------------------------------|--|

| | |
|------------------------------------|--|
| Reproductive toxicity - Assessment | : Weight of evidence does not support classification for reproductive toxicity |
|------------------------------------|--|

Aluminium hydroxide:

| | |
|----------------------|--|
| Effects on fertility | : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat |
|----------------------|--|

SAFETY DATA SHEET



Ti-Pure™ R-350 Titanium Dioxide Pigment

| | | | |
|----------------|------------------------------|------------------------------|---|
| Version 4.3 | Revision Date: 2023/12/11 | SDS Number: 1583657-00017 | Date of last issue: 2023/04/11 Date of first issue: 2017/04/21 |
|----------------|------------------------------|------------------------------|---|

Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Result: negative

STOT - single exposure

Not classified based on available information.

Components:

Titanium dioxide:

Exposure routes : Skin contact
Assessment : No significant health effects observed in animals at concentrations of 2000 mg/kg bw or less

Exposure routes : Ingestion
Assessment : No significant health effects observed in animals at concentrations of 2000 mg/kg bw or less

Exposure routes : inhalation (dust/mist/fume)
Assessment : No significant health effects observed in animals at concentrations of 5.0 mg/l/4h or less

STOT - repeated exposure

Not classified based on available information.

Components:

Titanium dioxide:

Exposure routes : Ingestion
Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Exposure routes : inhalation (dust/mist/fume)
Assessment : No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

Exposure routes : Ingestion
Assessment : No significant health effects observed in animals at concentrations of 200 mg/kg bw or less.

Repeated dose toxicity

Components:

Titanium dioxide:

SAFETY DATA SHEET



Ti-Pure™ R-350 Titanium Dioxide Pigment

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 2023/04/11 |
| 4.3 | 2023/12/11 | 1583657-00017 | Date of first issue: 2017/04/21 |

Species : Rat, male and female
NOAEL : 24,000 mg/kg
LOAEL : > 24,000 mg/kg
Application Route : Ingestion
Exposure time : 28 Days
Method : OECD Test Guideline 407
Remarks : No significant adverse effects were reported

Species : Rat, male and female
NOAEL : 0.01 mg/l
LOAEL : 0.5 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 24 Months
Method : OECD Test Guideline 453
Remarks : No significant adverse effects were reported

Species : Rat, male and female
NOAEL : 962 mg/kg
LOAEL : > 962 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408
Remarks : No significant adverse effects were reported

Silicon dioxide, amorphous:

Species : Rat
NOAEL : 1.3 mg/m³
Application Route : inhalation (dust/mist/fume)
Exposure time : 13 Weeks

Aluminium hydroxide:

Species : Rat
NOAEL : > 100 mg/kg
Application Route : Ingestion
Exposure time : 364 Days
Method : OECD Test Guideline 426
Remarks : Based on data from similar materials

Species : Rat
NOAEL : > 0.2 mg/kg
Application Route : inhalation (dust/mist/fume)
Exposure time : 12 Months
Remarks : Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

Components:

Titanium dioxide:

No aspiration toxicity classification

Ti-Pure™ R-350 Titanium Dioxide Pigment

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 4.3 | 2023/12/11 | 1583657-00017 | 2023/04/11 |
| | | | Date of first issue: 2017/04/21 |

12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Titanium dioxide:**

| | | |
|---|---|--|
| Toxicity to fish | : | LC50 (Fish): > 1,000 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 LC50 (Marine species): > 10,000 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia sp. (water flea)): > 1,000 mg/l Exposure time: 48 h Method: OECD Test Guideline 202 EC50 (No species specified): > 1,000 mg/l Exposure time: 48 h Method: OECD Test Guideline 202 |
| Toxicity to algae/aquatic plants | : | ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l Exposure time: 72 h Method: ISO 10253 NOEC (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l Exposure time: 3 d Method: OECD Test Guideline 201 NOEC (Skeletonema costatum (marine diatom)): 5,600 mg/l Exposure time: 3 d Method: ISO 10253 |

Silicon dioxide, amorphous:

| | | |
|---|---|---|
| Toxicity to fish | : | LC50 (Danio rerio (zebra fish)): > 10,000 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): > 1,000 mg/l Exposure time: 24 h Method: OECD Test Guideline 202 |

SAFETY DATA SHEET



Ti-Pure™ R-350 Titanium Dioxide Pigment

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 2023/04/11 |
| 4.3 | 2023/12/11 | 1583657-00017 | Date of first issue: 2017/04/21 |

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOEC (Desmodesmus subspicatus (green algae)): 10,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Aluminium hydroxide:

Toxicity to fish : LL50 (Salmo trutta (brown trout)): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EL50 (Selenastrum capricornutum (green algae)): > 100 mg/l
Exposure time: 96 h

Persistence and degradability

No data available

Bioaccumulative potential

Components:

Titanium dioxide:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
Bioconcentration factor (BCF): 352

Mobility in soil

No data available

Other adverse effects

No data available

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SAFETY DATA SHEET



Ti-Pure™ R-350 Titanium Dioxide Pigment

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 2023/04/11 |
| 4.3 | 2023/12/11 | 1583657-00017 | Date of first issue: 2017/04/21 |

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

| | |
|----------------------|------------------|
| UN number | : Not applicable |
| Proper shipping name | : Not applicable |
| Class | : Not applicable |
| Subsidiary risk | : Not applicable |
| Packing group | : Not applicable |
| Labels | : Not applicable |

IATA-DGR

| | |
|--|------------------|
| UN/ID No. | : Not applicable |
| Proper shipping name | : Not applicable |
| Class | : Not applicable |
| Subsidiary risk | : Not applicable |
| Packing group | : Not applicable |
| Labels | : Not applicable |
| Packing instruction (cargo aircraft) | : Not applicable |
| Packing instruction (passenger aircraft) | : Not applicable |

IMDG-Code

| | |
|----------------------|------------------|
| UN number | : Not applicable |
| Proper shipping name | : Not applicable |
| Class | : Not applicable |
| Subsidiary risk | : Not applicable |
| Packing group | : Not applicable |
| Labels | : Not applicable |
| EmS Code | : Not applicable |
| Marine pollutant | : Not applicable |

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

Not applicable

15. REGULATORY INFORMATION

National regulatory information

Regulations on Occupational Safety and Health Facilities
Standards for the Storage, Cleanup, Handling and Disposal of Industrial Waste
Standards of Permissible Exposure Limits in Workplace

16. OTHER INFORMATION

Other information : Ti-Pure™ and any associated logos are trademarks or copy-

SAFETY DATA SHEET



Ti-Pure™ R-350 Titanium Dioxide Pigment

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: |
| 4.3 | 2023/12/11 | 1583657-00017 | 2023/04/11 |
| | | | Date of first issue: 2017/04/21 |

rights of The Chemours Company FC, LLC.
Chemours™ and the Chemours Logo are trademarks of The Chemours Company.
Before use read Chemours safety information.
For further information contact the local Chemours office or nominated distributors.
These products may not be directly added to food, pharmaceuticals, cosmetics, or cigarette papers/filters for tobacco products.
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.
An electrostatic charge can potentially build up when pouring or conveying product from plastic bags. Do not use plastic bags in the presence of flammable or explosive vapors.
In the manufacture of titanium dioxide, product is packaged at temperatures of approximately 100 to 120°C (212 to 248°F).
When pigment is shipped shortly after manufacture, it may stay hot for a very long time depending on ambient temperatures and inventory storage practices. Use caution while handling hot pigment to prevent burns to personnel. Use caution in solvent applications to prevent ignition of solvent.

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Responsible Department : 130000030909
The Chemours (Taiwan) Company Limited
Product Sustainability Department
14th Floor, Hung Kuo Building, 167 Tun Hwa North Road,
Taipei, Taiwan

Prepared by : 0080-112-7758
Zhenwen Tu / Product Stewardship and Regulatory Compliance Expert

Revision Date : 2023/12/11

Date format : yyyy/mm/dd

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
TW OEL : Standards of Permissible Exposure Limits in Workplace

ACGIH / TWA : 8-hour, time-weighted average

SAFETY DATA SHEET



Ti-Pure™ R-350 Titanium Dioxide Pigment

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 2023/04/11 |
| 4.3 | 2023/12/11 | 1583657-00017 | Date of first issue: 2017/04/21 |

TW OEL / TWA : 8-hour time weighted average
TW OEL / STEL : time weighted average for short term exposure

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

TW / EN