

SAFETY DATA SHEET



Fluorocarbon 152a Aerosol Propellant

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 14.04.2023 |
| 5.15 | 08.06.2023 | 1324510-00046 | Date of first issue: 27.02.2017 |

SECTION 1: Identification of the hazardous chemical and of the supplier

Product identifier

| | | |
|---------------|---|--------------------------------------|
| Product name | : | Fluorocarbon 152a Aerosol Propellant |
| Chemical name | : | 1,1-Difluoroethane |
| CAS-No. | : | 75-37-6 |
| Product code | : | |
| SDS-Identcode | : | 130000000099 |

Recommended use of the chemical and restrictions on use

| | | |
|---------------------|---|--------------------------|
| Recommended use | : | Propellant |
| Restrictions on use | : | For industrial use only. |

Manufacturer or supplier's details



| | | |
|----------------------------|---|---|
| Company | : | The Chemours Malaysia Sdn. Bhd. |
| Address | : | Suite 20-01 & 20-02B, Level 20, The Pinnacle, Persiaran Lagoon, Bandar Sunway, Subang Jaya Selangor Darul Ehsan 47500 Malaysia |
| Telephone | : | +60 3 5021 0178 |
| Emergency telephone number | : | 1-800-815-308 |
| Telefax | : | +60 3 2178 4719 |

SECTION 2: Hazards identification

Classification of the hazardous chemical

| | | |
|----------------------|---|---------------|
| Flammable gases | : | Category 1 |
| Gases under pressure | : | Liquefied gas |

Label elements

| | | |
|-------------------|---|---|
| Hazard pictograms | : |   |
|-------------------|---|---|

| | | |
|-------------|---|--------|
| Signal word | : | Danger |
|-------------|---|--------|

| | | |
|-------------------|---|-------------------------------|
| Hazard statements | : | H220 Extremely flammable gas. |
|-------------------|---|-------------------------------|

SAFETY DATA SHEET



Fluorocarbon 152a Aerosol Propellant

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 14.04.2023 |
| 5.15 | 08.06.2023 | 1324510-00046 | Date of first issue: 27.02.2017 |

H280 Contains gas under pressure; may explode if heated.

Precautionary statements

:

Prevention:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.
No smoking.

Response:

P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381 Eliminate all ignition sources if safe to do so.

Storage:

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

Other hazards which do not result in classification

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.

Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.

Rapid evaporation of the product may cause frostbite.

May displace oxygen and cause rapid suffocation.

SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture

: Substance

Components

| Chemical name | CAS-No. | Concentration (% w/w) |
|--------------------|---------|-----------------------|
| 1,1-Difluoroethane | 75-37-6 | >= 60 -<= 100 |

SECTION 4: First aid measures

General advice

: In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled

: If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention immediately.

In case of skin contact

: Thaw frosted parts with lukewarm water. Do not rub affected area.
Get medical attention immediately.

In case of eye contact

: Get medical attention immediately.

If swallowed

: Ingestion is not considered a potential route of exposure.

Most important symptoms

: May cause cardiac arrhythmia.

Fluorocarbon 152a Aerosol Propellant

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 14.04.2023 |
| 5.15 | 08.06.2023 | 1324510-00046 | Date of first issue: 27.02.2017 |

and effects, both acute and delayed

Other symptoms potentially related to misuse or inhalation abuse are
Cardiac sensitisation
Anaesthetic effects
Light-headedness
Dizziness
confusion
Lack of coordination
Drowsiness
Unconsciousness
Gas reduces oxygen available for breathing.
Contact with liquid or refrigerated gas can cause cold burns and frostbite.

Protection of first-aiders : No special precautions are necessary for first aid responders.

Notes to physician : Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, that may be used in situations of emergency life support should be used with special caution.

SECTION 5: Firefighting measures**Extinguishing media**

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

Physicochemical hazards arising from the chemical

Specific hazards during fire-fighting : Vapours may form flammable mixture with air
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Hydrogen fluoride
carbonyl fluoride
Carbon oxides

Special protective equipment and precautions for fire-fighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fight fire remotely due to the risk of explosion.
Use water spray to cool unopened containers.
Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

SAFETY DATA SHEET



Fluorocarbon 152a Aerosol Propellant

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 14.04.2023 |
| 5.15 | 08.06.2023 | 1324510-00046 | Date of first issue: 27.02.2017 |

Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Hazchem Code : 2YE

SECTION 6: Accidental release measures

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Only trained personnel should re-enter the area.
Remove all sources of ignition.
Avoid skin contact with leaking liquid (danger of frostbite).
Ventilate the area.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
- Methods and materials for containment and cleaning up : Ventilate the area.
Non-sparking tools should be used.
Suppress (knock down) gases/vapours/mists with a water spray jet.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7: Handling and storage

Handling

Precautions for safe handling

- Technical measures : Use equipment rated for cylinder pressure. Use a backflow preventative device in piping. Close valve after each use and when empty.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.
- Advice on safe handling : Avoid breathing gas.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Wear cold insulating gloves/ face shield/ eye protection.
Valve protection caps and valve outlet threaded plugs must

Fluorocarbon 152a Aerosol Propellant

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 14.04.2023 |
| 5.15 | 08.06.2023 | 1324510-00046 | Date of first issue: 27.02.2017 |

remain in place unless container is secured with valve outlet piped to use point.
Prevent backflow into the gas tank.
Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder.
Use a pressure reducing regulator when connecting cylinder to lower pressure (<3000 psig) piping or systems.
Close valve after each use and when empty. Do NOT change or force fit connections.
Prevent the intrusion of water into the gas tank.
Never attempt to lift cylinder by its cap.
Do not drag, slide or roll cylinders.
Use a suitable hand truck for cylinder movement.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.

Storage**Conditions for safe storage, including any incompatibilities**

Conditions for safe storage : Cylinders should be stored upright and firmly secured to prevent falling or being knocked over.
Separate full containers from empty containers.
Do not store near combustible materials.
Avoid area where salt or other corrosive materials are present.
Keep in properly labelled containers.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Keep away from direct sunlight.
Store in accordance with the particular national regulations.
Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable liquids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Explosives

Recommended storage temperature : < 52 °C

Storage period : > 10 yr

Further information on storage stability : The product has an indefinite shelf life when stored properly.

Fluorocarbon 152a Aerosol Propellant

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 14.04.2023 |
| 5.15 | 08.06.2023 | 1324510-00046 | Date of first issue: 27.02.2017 |

SECTION 8: Exposure controls and personal protection**Control parameters**

Contains no substances with occupational exposure limit values.

Appropriate engineering controls : Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Individual protection measures, such as personal protective equipment

Eye/face protection : Wear the following personal protective equipment:
Chemical resistant goggles must be worn.
Face-shield

Skin protection : Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.

Hand protection
Material : Heat resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Organic gas and low boiling vapour type

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9: Physical and chemical properties

Appearance : Liquefied gas

SAFETY DATA SHEET



Fluorocarbon 152a Aerosol Propellant

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 14.04.2023 |
| 5.15 | 08.06.2023 | 1324510-00046 | Date of first issue: 27.02.2017 |

| | | |
|--|---|--|
| Colour | : | clear, colourless |
| Odour | : | slight |
| Odour Threshold | : | No data available |
| pH | : | No data available |
| Melting point/freezing point | : | -117 °C |
| Initial boiling point and boiling range | : | -24.7 °C (1,013 hPa) |
| Flash point | : | Not applicable |
| Evaporation rate | : | Not applicable |
| Flammability (solid, gas) | : | Flammable |
| Self-ignition | : | The substance or mixture is not classified as pyrophoric. |
| Upper explosion limit / Upper flammability limit | : | Upper flammability limit 16.9 %(V) Method: ASTM E681 |
| Lower explosion limit / Lower flammability limit | : | Lower flammability limit 3.9 %(V) Method: ASTM E681 |
| Vapour pressure | : | 5,146.24 hPa (25 °C) |
| Relative vapour density | : | 2.4 (Air = 1.0) |
| Relative density | : | 2.4 |
| Density | : | 0.911 g/cm ³ (20 °C) (as liquid) 0.83 g/cm ³ (50 °C) (as liquid) 0.0027 g/cm ³ (25 °C) (as liquid) |
| Solubility(ies) Water solubility | : | 0.28 g/l (25 °C) |
| Partition coefficient: n-octanol/water | : | log Pow: 1.13 (25 °C) |

SAFETY DATA SHEET



Fluorocarbon 152a Aerosol Propellant

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 14.04.2023 |
| 5.15 | 08.06.2023 | 1324510-00046 | Date of first issue: 27.02.2017 |

| | | |
|---------------------------|---|--|
| Auto-ignition temperature | : | 440 °C |
| Decomposition temperature | : | No data available |
| Viscosity | : | |
| Viscosity, kinematic | : | Not applicable |
| Explosive properties | : | Not explosive |
| Oxidizing properties | : | The substance or mixture is not classified as oxidizing. |
| Particle size | : | Not applicable |

SECTION 10: Stability and reactivity

| | | |
|------------------------------------|---|--|
| Reactivity | : | Not classified as a reactivity hazard. |
| Chemical stability | : | Stable if used as directed. Follow precautionary advice and avoid incompatible materials and conditions. |
| Possibility of hazardous reactions | : | Vapours may form flammable mixture with air Can react with strong oxidizing agents. Extremely flammable gas. |
| Conditions to avoid | : | Heat, flames and sparks. |
| Incompatible materials | : | Oxidizing agents |
| Hazardous decomposition products | : | No hazardous decomposition products are known. |

SECTION 11: Toxicological information

| | | |
|--|---|---|
| Information on likely routes of exposure | : | Inhalation Skin contact Eye contact |
|--|---|---|

Acute toxicity

Not classified based on available information.

Components:

1,1-Difluoroethane:

| | | |
|---------------------------|---|--|
| Acute oral toxicity | : | Assessment: The substance or mixture has no acute oral toxicity |
| Acute inhalation toxicity | : | LC50 (Rat): > 437500 ppm Exposure time: 4 h Test atmosphere: gas No observed adverse effect concentration (Dog): 50000 ppm Test atmosphere: gas Method: Cardiac sensitisation study |

SAFETY DATA SHEET



Fluorocarbon 152a Aerosol Propellant

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 14.04.2023 |
| 5.15 | 08.06.2023 | 1324510-00046 | Date of first issue: 27.02.2017 |

Lowest observed adverse effect concentration (Dog): 150000 ppm

Test atmosphere: gas

Method: Cardiac sensitisation study

Cardiac sensitisation threshold limit (Dog): 405,000 mg/m³

Test atmosphere: gas

Method: Cardiac sensitisation study

Acute dermal toxicity : Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:

1,1-Difluoroethane:

Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

1,1-Difluoroethane:

Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

1,1-Difluoroethane:

Exposure routes : Skin contact
Result : negative

Exposure routes : Inhalation
Species : Rat
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

1,1-Difluoroethane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

SAFETY DATA SHEET



Fluorocarbon 152a Aerosol Propellant

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 14.04.2023 |
| 5.15 | 08.06.2023 | 1324510-00046 | Date of first issue: 27.02.2017 |

Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: positive

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Carcinogenicity

Not classified based on available information.

Components:

1,1-Difluoroethane:

Species : Rat
Application Route : inhalation (gas)
Exposure time : 104 weeks
Method : OECD Test Guideline 453
Result : negative

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

Reproductive toxicity

Not classified based on available information.

Components:

1,1-Difluoroethane:

Effects on fertility : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: inhalation (gas)
Method: OECD Test Guideline 478
Result: negative
Remarks: Based on data from similar materials

Test Type: Combined Chronic Toxicity/Carcinogenicity Studies

Species: Rat

Application Route: inhalation (gas)

Method: OECD Test Guideline 453

Result: negative

Effects on foetal development : Test Type: Prenatal development toxicity study (teratogenicity)
Species: Rat

Fluorocarbon 152a Aerosol Propellant

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 14.04.2023 |
| 5.15 | 08.06.2023 | 1324510-00046 | Date of first issue: 27.02.2017 |

Application Route: inhalation (vapour)
Method: OECD Test Guideline 414
Result: negative

Test Type: Prenatal development toxicity study (teratogenicity)
Species: Rabbit
Application Route: inhalation (gas)
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity

STOT - single exposure

Not classified based on available information.

Components:**1,1-Difluoroethane:**

Exposure routes : inhalation (gas)
Assessment : No significant health effects observed in animals at concentrations of 20000 ppmV/4h or less

Exposure routes : Skin contact
Assessment : No significant health effects observed in animals at concentrations of 2000 mg/kg bw or less

Exposure routes : Ingestion
Assessment : No significant health effects observed in animals at concentrations of 2000 mg/kg bw or less

STOT - repeated exposure

Not classified based on available information.

Components:**1,1-Difluoroethane:**

Exposure routes : inhalation (gas)
Assessment : No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less.

Exposure routes : Skin contact
Assessment : No significant health effects observed in animals at concentrations of 200 mg/kg bw or less.

Exposure routes : Ingestion
Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Fluorocarbon 152a Aerosol Propellant

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 14.04.2023 |
| 5.15 | 08.06.2023 | 1324510-00046 | Date of first issue: 27.02.2017 |

Repeated dose toxicity**Components:****1,1-Difluoroethane:**

| | |
|-------------------|---------------------------|
| Species | : Rat, male and female |
| NOAEL | : 25000 ppm |
| LOAEL | : >25000 ppm |
| Application Route | : inhalation (gas) |
| Exposure time | : 104 Weeks |
| Method | : OECD Test Guideline 453 |

Aspiration toxicity

Not classified based on available information.

Components:**1,1-Difluoroethane:**

No aspiration toxicity classification

SECTION 12: Ecological information**Ecotoxicity****Components:****1,1-Difluoroethane:**

| | |
|---|--|
| Toxicity to fish | : LC50 (Fish): 295.783 mg/l Exposure time: 96 h Method: ECOSAR (Ecological Structure Activity Relationships) |
| Toxicity to daphnia and other aquatic invertebrates | : EC50 (Daphnia (water flea)): 146.695 mg/l Exposure time: 48 h Method: ECOSAR (Ecological Structure Activity Relationships) |
| Toxicity to algae/aquatic plants | : EC50 (algae): 47.755 mg/l Method: ECOSAR (Ecological Structure Activity Relationships) |

Ecotoxicology Assessment

| | |
|--------------------------|---|
| Acute aquatic toxicity | : This product has no known ecotoxicological effects. |
| Chronic aquatic toxicity | : This product has no known ecotoxicological effects. |

Persistence and degradability**Components:****1,1-Difluoroethane:**

| | |
|------------------|--------------------------------------|
| Biodegradability | : Result: Not readily biodegradable. |
|------------------|--------------------------------------|

SAFETY DATA SHEET



Fluorocarbon 152a Aerosol Propellant

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 14.04.2023 |
| 5.15 | 08.06.2023 | 1324510-00046 | Date of first issue: 27.02.2017 |

Bioaccumulative potential

Components:

1,1-Difluoroethane:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 1.13 (25 °C)

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13: Disposal information

Disposal methods

Waste from residues : Disposal of waste to be in accordance with the Environmental Quality (Scheduled Wastes) Regulations and other guidelines issuance by DOE and/or local authorities.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty pressure vessels should be returned to the supplier.
If not otherwise specified: Dispose of as unused product.

SECTION 14: Transport information

International Regulations

UNRTDG

UN number : UN 1030
Proper shipping name : 1,1-DIFLUOROETHANE
Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1

IATA-DGR

UN/ID No. : UN 1030
Proper shipping name : 1,1-Difluoroethane
Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo aircraft) : 200
Packing instruction (passenger aircraft) : Not permitted for transport

IMDG-Code

UN number : UN 1030
Proper shipping name : 1,1-DIFLUOROETHANE

SAFETY DATA SHEET



Fluorocarbon 152a Aerosol Propellant

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 14.04.2023 |
| 5.15 | 08.06.2023 | 1324510-00046 | Date of first issue: 27.02.2017 |

| | |
|------------------|------------------------------|
| Class | : 2.1 |
| Packing group | : Not assigned by regulation |
| Labels | : 2.1 |
| EmS Code | : F-D, S-U |
| Marine pollutant | : no |

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Hazchem Code : 2YE

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15: Regulatory information

Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

Montreal Protocol : 1,1-Difluoroethane

SECTION 16: Other information

Revision Date : 08.06.2023

Other information : Chemours™ and the Chemours Logo are trademarks of The Chemours Company.
Before use read Chemours safety information.
For further information contact the local Chemours office or nominated distributors.

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Date format : dd.mm.yyyy

Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with

SAFETY DATA SHEET



Fluorocarbon 152a Aerosol Propellant

| | | | |
|---------|----------------|---------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 14.04.2023 |
| 5.15 | 08.06.2023 | 1324510-00046 | Date of first issue: 27.02.2017 |

x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

MY / EN