

# SAFETY DATA SHEET

according to the Globally Harmonized System



## Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 24.03.2023
4.1	25.09.2023	4185186-00013	Date of first issue: 23.04.2019

---

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Opteon™ XP30 (R-514A) Refrigerant

SDS-Identcode : 130000144003

#### Manufacturer or supplier's details

Company : The Chemours India Private Limited

Address : Gala Impecca, 1st Floor, Opposite Sangam Big Cinema, Andheri Kurla Road, Chakala, Andheri East, Maharashtra  
Mumbai – 400069 India

Telephone : 91 22 6227 3300

Emergency telephone number : 000 800 100 7141 (Chemtrec) or 91 22 6227 3300

#### Recommended use of the chemical and restrictions on use

Recommended use : Refrigerant  
Heat transfer fluids

Restrictions on use : For professional and industrial installation and use only.

---

### 2. HAZARDS IDENTIFICATION

#### Manufacture, Storage and Import of Hazardous Chemicals Rules 1989

##### Classification

Not classified as hazardous according to criteria laid down in Part I of Schedule-1.

##### GHS Classification

Skin corrosion/irritation : Category 3

Serious eye damage/eye irritation : Category 2B

Specific target organ toxicity - single exposure : Category 3

Short-term (acute) aquatic hazard : Category 3

##### GHS label elements

# SAFETY DATA SHEET

according to the Globally Harmonized System



## Opteon™ XP30 (R-514A) Refrigerant

Version 4.1      Revision Date: 25.09.2023      SDS Number: 4185186-00013      Date of last issue: 24.03.2023  
Date of first issue: 23.04.2019

Hazard pictograms

:



Signal word

:

Warning

Hazard statements

:

H316 Causes mild skin irritation.  
H320 Causes eye irritation.  
H336 May cause drowsiness or dizziness.  
H402 Harmful to aquatic life.

Precautionary statements

:

### Prevention:

P261 Avoid breathing mist or vapours.  
P264+P265 Wash hands thoroughly after handling. Do not touch eyes.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.

### Response:

P304 + P340 + P319 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical help if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P332 + P317 If skin irritation occurs: Get medical help.  
P337 + P317 If eye irritation persists: Get medical help.

### Storage:

P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards which do not result in classification

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.

Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.

Rapid evaporation of the product may cause frostbite.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
(Z)-1,1,1,4,4,4-Hexafluoro-2-butene#	692-49-9	75.1
Trans-Dichloroethylene	156-60-5	24.9

# SAFETY DATA SHEET

according to the Globally Harmonized System



## Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 24.03.2023
4.1	25.09.2023	4185186-00013	Date of first issue: 23.04.2019

#: Voluntarily-disclosed substance

### 4. FIRST AID MEASURES

- |   |  |
|---|--|
| General advice  | : In the case of accident or if you feel unwell, seek medical advice immediately.<br>When symptoms persist or in all cases of doubt seek medical advice.   |
| If inhaled  | : If inhaled, remove to fresh air.<br>Get medical attention if symptoms occur.   |
| In case of skin contact                                     | : In case of contact, immediately flush skin with plenty of water.<br>Remove contaminated clothing and shoes.<br>Get medical attention.<br>Wash clothing before reuse.<br>Thoroughly clean shoes before reuse.   |
| In case of eye contact                                      | : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.<br>If easy to do, remove contact lens, if worn.<br>Get medical attention.   |
| If swallowed  | : If swallowed, DO NOT induce vomiting.<br>Get medical attention if symptoms occur.<br>Rinse mouth thoroughly with water.  |
| Most important symptoms and effects, both acute and delayed | : May cause cardiac arrhythmia.<br>Other symptoms potentially related to misuse or inhalation abuse are<br>Cardiac sensitisation<br>Anaesthetic effects<br>Light-headedness<br>Dizziness<br>confusion<br>Lack of coordination<br>Drowsiness<br>Unconsciousness<br>Skin contact may provoke the following symptoms:<br>Irritation<br>Swelling of tissue<br>Itching<br>Discomfort<br>Redness<br>Eye contact may provoke the following symptoms<br>tearing<br>Redness<br>Discomfort<br>Causes mild skin irritation.<br>Causes eye irritation.<br>May cause drowsiness or dizziness. |
| Protection of first-aiders                                  | : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).  |

# SAFETY DATA SHEET

according to the Globally Harmonized System



## Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 24.03.2023
4.1	25.09.2023	4185186-00013	Date of first issue: 23.04.2019

Notes to physician : Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, that may be used in situations of emergency life support should be used with special caution.

### 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Hydrogen fluoride  
carbonyl fluoride  
Carbon oxides  
Chlorine compounds

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.  
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.

# SAFETY DATA SHEET

according to the Globally Harmonized System



## Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 24.03.2023
4.1	25.09.2023	4185186-00013	Date of first issue: 23.04.2019

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### 7. HANDLING AND STORAGE

- |  |   |  |
|--|---|--|
| Technical measures                       | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.  |
| Local/Total ventilation                  | : | If sufficient ventilation is unavailable, use with local exhaust ventilation.  |
| Advice on safe handling                  | : | Do not get on skin or clothing.<br>Avoid breathing mist or vapours.<br>Do not swallow.<br>Do not get in eyes.<br>Wash skin thoroughly after handling.<br>Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment<br>Take care to prevent spills, waste and minimize release to the environment.   |
| Conditions for safe storage              | : | Do not expose drums to direct heat or temperature above 46°C (115°F) to avoid pressurizing and possibly distorting the drums.<br>Material should not be dispensed by pouring from pail/drum shipping containers containing 5 gallons or more. The use of a drum pump is recommended for dispensing from pail/drum shipping containers with 5 gallons or more, except for smaller containers where adequate ventilation can be used to manage the exposure.<br>Keep in properly labelled containers.<br>Store locked up.<br>Keep in a cool, well-ventilated place.<br>Store in accordance with the particular national regulations. |
| Materials to avoid                       | : | No special restrictions on storage with other products.  |
| Recommended storage temperature          | : | < 46 °C  |
| Storage period                           | : | > 10 yr  |
| Further information on storage stability | : | The product has an indefinite shelf life when stored properly.   |

Keep away from direct sunlight.

# SAFETY DATA SHEET

according to the Globally Harmonized System



## Opteon™ XP30 (R-514A) Refrigerant

Version 4.1      Revision Date: 25.09.2023      SDS Number: 4185186-00013      Date of last issue: 24.03.2023  
Date of first issue: 23.04.2019

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Trans-Dichloroethylene	156-60-5	TWA	200 ppm	ACGIH

**Engineering measures** : Minimize workplace exposure concentrations.  
If sufficient ventilation is unavailable, use with local exhaust ventilation.

#### Personal protective equipment

**Respiratory protection** : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

**Filter type** : Organic gas and low boiling vapour type

#### Hand protection

**Material** : Chemical-resistant gloves

**Remarks** : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

**Eye protection** : Wear the following personal protective equipment:  
Safety goggles

**Skin and body protection** : Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.

**Hygiene measures** : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** : liquid

# SAFETY DATA SHEET

according to the Globally Harmonized System



## Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 24.03.2023
4.1	25.09.2023	4185186-00013	Date of first issue: 23.04.2019

---

Colour	:	clear
Odour	:	slight, ether-like
Odour Threshold	:	No data available
pH	:	7
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	29.1 °C
Flash point	:	Method: ASTM D 56 does not flash
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	No data available
Upper explosion limit / Upper flammability limit	:	Upper flammability limit Method: ASTM E681 None.
Lower explosion limit / Lower flammability limit	:	Lower flammability limit Method: ASTM E681 None.
Vapour pressure	:	871.4 hPa (25 °C)
Relative vapour density	:	5.01 (Air = 1.0)
Relative density	:	1.31 (25 °C)
Density	:	1.308 g/cm <sup>3</sup> (25 °C)
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	

# SAFETY DATA SHEET

according to the Globally Harmonized System



## Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 24.03.2023
4.1	25.09.2023	4185186-00013	Date of first issue: 23.04.2019

Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	Not applicable

### 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	None known.
Conditions to avoid	:	None known.
Incompatible materials	:	None.
Hazardous decomposition products	:	No hazardous decomposition products are known.

### 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure :

- Inhalation
- Skin contact
- Ingestion
- Eye contact

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **(Z)-1,1,1,4,4,4-Hexafluoro-2-butene:**

Acute inhalation toxicity : LC50 (Rat): > 690.413 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403

No observed adverse effect concentration (Dog): 12500 ppm  
Test atmosphere: gas

Lowest observed adverse effect concentration (Dog): 25000 ppm  
Test atmosphere: gas

Cardiac sensitisation threshold limit (Dog): 1,677,740 mg/m<sup>3</sup>  
Test atmosphere: gas



# SAFETY DATA SHEET

according to the Globally Harmonized System



## Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 24.03.2023
4.1	25.09.2023	4185186-00013	Date of first issue: 23.04.2019

---

### Trans-Dichloroethylene:

Acute oral toxicity : LD50 (Rat): 7,902 mg/kg  
Method: OECD Test Guideline 420

Acute inhalation toxicity : LC50 (Rat): 95.5 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403

Lowest observed adverse effect concentration (Dog): 250000 ppm  
Test atmosphere: gas

Cardiac sensitisation threshold limit (Dog): 991,309 mg/m3  
Test atmosphere: gas

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Method: OECD Test Guideline 402

### Skin corrosion/irritation

Causes mild skin irritation.

#### Components:

#### (Z)-1,1,1,4,4,4-Hexafluoro-2-butene:

Result : No skin irritation

### Trans-Dichloroethylene:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Mild skin irritation

### Serious eye damage/eye irritation

Causes eye irritation.

#### Components:

#### (Z)-1,1,1,4,4,4-Hexafluoro-2-butene:

Result : No eye irritation

### Trans-Dichloroethylene:

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : Irritation to eyes, reversing within 7 days

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

# SAFETY DATA SHEET

according to the Globally Harmonized System



## Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 24.03.2023
4.1	25.09.2023	4185186-00013	Date of first issue: 23.04.2019

---

### Respiratory sensitisation

Not classified based on available information.

### Components:

#### (Z)-1,1,1,4,4,4-Hexafluoro-2-butene:

Exposure routes	:	Skin contact
Result	:	negative

### Germ cell mutagenicity

Not classified based on available information.

### Components:

#### (Z)-1,1,1,4,4,4-Hexafluoro-2-butene:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
-----------------------	---	---

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Genotoxicity in vivo	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: inhalation (vapour) Method: OECD Test Guideline 474 Result: negative
----------------------	---	---

Germ cell mutagenicity - Assessment	:	Weight of evidence does not support classification as a germ cell mutagen.
-------------------------------------	---	--

#### Trans-Dichloroethylene:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
-----------------------	---	---

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

Genotoxicity in vivo	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse
----------------------	---	--

# SAFETY DATA SHEET

according to the Globally Harmonized System



## Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 24.03.2023
4.1	25.09.2023	4185186-00013	Date of first issue: 23.04.2019

---

Application Route: Ingestion  
Method: OECD Test Guideline 474  
Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

### **Carcinogenicity**

Not classified based on available information.

### **Reproductive toxicity**

Not classified based on available information.

### **Components:**

#### **(Z)-1,1,1,4,4,4-Hexafluoro-2-butene:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Method: OECD Test Guideline 416  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Method: OECD Test Guideline 414  
Result: negative

Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity, No effects on or via lactation

#### **Trans-Dichloroethylene:**

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: Inhalation  
Method: OECD Test Guideline 414  
Result: negative

### **STOT - single exposure**

May cause drowsiness or dizziness.

### **Components:**

#### **Trans-Dichloroethylene:**

Assessment : May cause drowsiness or dizziness.

### **STOT - repeated exposure**

Not classified based on available information.

### **Components:**

#### **(Z)-1,1,1,4,4,4-Hexafluoro-2-butene:**

Exposure routes : inhalation (vapour)

# SAFETY DATA SHEET

according to the Globally Harmonized System



## Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 24.03.2023
4.1	25.09.2023	4185186-00013	Date of first issue: 23.04.2019

Assessment : No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or less.

### Trans-Dichloroethylene:

Exposure routes : Inhalation  
Assessment : No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less.

Exposure routes : Ingestion  
Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

### Repeated dose toxicity

#### Components:

##### **(Z)-1,1,1,4,4,4-Hexafluoro-2-butene:**

Species : Rat, male and female  
NOAEL : 33.5 mg/l  
LOAEL : 50.3 mg/l  
Application Route : inhalation (vapour)  
Exposure time : 90 d  
Method : OECD Test Guideline 413

##### **Trans-Dichloroethylene:**

Species : Rat, male and female  
NOAEL : 4000 ppm  
LOAEL : > 4000 ppm  
Application Route : Inhalation  
Exposure time : 90 Days  
Method : OECD Test Guideline 413

Species : Rat, male and female  
NOAEL : 3,210 mg/kg  
LOAEL : > 3,210 mg/kg  
Application Route : Ingestion  
Exposure time : 98 Days  
Method : OECD Test Guideline 408

### Aspiration toxicity

Not classified based on available information.

#### Components:

##### **(Z)-1,1,1,4,4,4-Hexafluoro-2-butene:**

No aspiration toxicity classification

# SAFETY DATA SHEET

according to the Globally Harmonized System



## Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 24.03.2023
4.1	25.09.2023	4185186-00013	Date of first issue: 23.04.2019

### 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

##### Components:

##### **(Z)-1,1,1,4,4,4-Hexafluoro-2-butene:**

- Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): 76.1 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 22.5 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : ErC50 ( Pseudokirchneriella subcapitata (green algae)): > 23.7 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201
- NOEC ( Pseudokirchneriella subcapitata (green algae)): 6.92 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201
- Toxicity to fish (Chronic toxicity) : NOEC: 10 mg/l  
Exposure time: 32 d  
Species: Gobicypris rarus (rare gudgeon)  
Method: OECD Test Guideline 210
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 10 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211

##### **Trans-Dichloroethylene:**

- Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 135 mg/l  
Exposure time: 96 h  
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 220 mg/l  
Exposure time: 48 h  
Method: EPA-660/3-75-009
- Toxicity to algae/aquatic plants : EbC50 ( Pseudokirchneriella subcapitata (green algae)): 36.36 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 201

# SAFETY DATA SHEET

according to the Globally Harmonized System



## Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 24.03.2023
4.1	25.09.2023	4185186-00013	Date of first issue: 23.04.2019

---

### Persistence and degradability

#### Components:

##### **(Z)-1,1,1,4,4,4-Hexafluoro-2-butene:**

Biodegradability : Result: Not readily biodegradable.  
Method: OECD Test Guideline 302C

##### **Trans-Dichloroethylene:**

Biodegradability : Result: not rapidly degradable  
Method: OECD Test Guideline 301D

### Bioaccumulative potential

#### Components:

##### **(Z)-1,1,1,4,4,4-Hexafluoro-2-butene:**

Partition coefficient: n- : log Pow: 2.3  
octanol/water

##### **Trans-Dichloroethylene:**

Partition coefficient: n- : log Pow: 2.06  
octanol/water

### Mobility in soil

No data available

### Other adverse effects

No data available

---

## 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Do not dispose of waste into sewer.  
Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

---

## 14. TRANSPORT INFORMATION

### International Regulations

#### **UNRTDG**

Not regulated as a dangerous good

#### **IATA-DGR**

Not regulated as a dangerous good

# SAFETY DATA SHEET

according to the Globally Harmonized System



## Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 24.03.2023
4.1	25.09.2023	4185186-00013	Date of first issue: 23.04.2019

### IMDG-Code

Not regulated as a dangerous good

### Transport in bulk according to IMO instruments

Not applicable for product as supplied.

### Special precautions for user

Not applicable

## 15. REGULATORY INFORMATION

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

## 16. OTHER INFORMATION

Revision Date : 25.09.2023

Other information : Opteon™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.  
Chemours™ and the Chemours Logo are trademarks of The Chemours Company.  
Before use read Chemours safety information.  
For further information contact the local Chemours office or nominated distributors.

### Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Date format : dd.mm.yyyy

### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIH / TWA : 8-hour, time-weighted average

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Or-

# SAFETY DATA SHEET

according to the Globally Harmonized System



## Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 24.03.2023
4.1	25.09.2023	4185186-00013	Date of first issue: 23.04.2019

---

ganisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

IN / EN