

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2023
9.0	26.10.2023	1330011-00046	Date of first issue: 27.02.2017

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Viton™ VTR-9208 fluoroelastomer

SDS-Identcode : 130000025200

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Manufacture of rubber products

Recommended restrictions  
on use : Not applicable

#### 1.3 Details of the supplier of the safety data sheet

Company : Chemours Netherlands B.V.  
Baanhoekweg 22  
3313 LA Dordrecht Netherlands

Telephone : +31-(0)-78-630-1011

Telefax : +31-78-6163737

E-mail address of person  
responsible for the SDS : sds-support@chemours.com

#### 1.4 Emergency telephone number

+(353)-19014670 (CHEMTREC - Recommended) ; +353-(01) 809 2166 (Poison Information  
Center of Ireland)

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.
--	--

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard statements : H412 Harmful to aquatic life with long lasting effects.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2023
9.0	26.10.2023	1330011-00046	Date of first issue: 27.02.2017

Supplemental Hazard Statements : EUH070 Toxic by eye contact.

Precautionary statements : **Prevention:**  
P273 Avoid release to the environment.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Reaction mass of 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]diphenol and benzyltriphenylphosphonium, salt with 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis[phenol] (1:1)	Not Assigned  01-2120763412-59-0000	Repr. 1B; H360 STOT RE 2; H373 (Seminal vesicle, Prostate) Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 10	>= 2.5 - < 10
4,4'-(Hexafluoroisopropylidene)diphenol	1478-61-1 216-036-7 01-2120762844-45-0004	Eye Dam. 1; H318 Repr. 1B; H360 STOT RE 2; H373 (Prostate, Seminal vesicle) Aquatic Chronic 1; H410  M-Factor (Chronic	>= 0.3 - < 1

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version 9.0      Revision Date: 26.10.2023      SDS Number: 1330011-00046      Date of last issue: 07.05.2023  
Date of first issue: 27.02.2017

		aquatic toxicity): 1	
Benzyltriphenylphosphonium chloride	1100-88-5 214-154-3 01-2120759336-47	Acute Tox. 2; H300 Acute Tox. 2; H330 Eye Dam. 1; H318 STOT SE 3; H335 STOT RE 1; H372 (Lungs, nasal cavity) Aquatic Acute 1; H400 Aquatic Chronic 1; H410 EUH070  M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1  Acute toxicity esti- mate  Acute oral toxicity: 43 mg/kg	$\geq 0.25 - < 1$

For explanation of abbreviations see section 16.

### Alternative CAS Numbers for some regions

Chemical name	Alternative CAS Number(s)
Reaction mass of 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]diphenol and benzyltriphenylphosphonium, salt with 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis[phenol] (1:1)	75768-65-9, 1478-61-1

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- Protection of first-aiders : No special precautions are necessary for first aid responders.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : Wash with water and soap as a precaution.  
Get medical attention if symptoms occur.
- In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2023
9.0	26.10.2023	1330011-00046	Date of first issue: 27.02.2017

---

If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.

### 4.2 Most important symptoms and effects, both acute and delayed

Risks : Toxic by eye contact.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : None known.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides  
Fluorine compounds

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2023
9.0	26.10.2023	1330011-00046	Date of first issue: 27.02.2017

---

### 6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Avoid contact with eyes.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Take care to prevent spills, waste and minimize release to the environment.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep in properly labelled containers. Store in accordance with the particular national regulations.

Advice on common storage : No special restrictions on storage with other products.

### 7.3 Specific end use(s)

Specific use(s) : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version 9.0      Revision Date: 26.10.2023      SDS Number: 1330011-00046      Date of last issue: 07.05.2023  
Date of first issue: 27.02.2017

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Reaction mass of 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]diphenol and benzyltriphenylphosphonium, salt with 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis[phenol] (1:1)	Workers	Inhalation	Long-term systemic effects	0.118 mg/m3
	Workers	Skin contact	Long-term systemic effects	0.033 mg/kg bw/day
4,4'-(Hexafluoroisopropylidene)diphenol	Workers	Inhalation	Long-term systemic effects	0.118 mg/m3
	Workers	Skin contact	Long-term systemic effects	0.033 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0.029 mg/m3
	Consumers	Dermal	Long-term systemic effects	0.017 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.017 mg/kg bw/day

#### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Reaction mass of 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]diphenol and benzyltriphenylphosphonium, salt with 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis[phenol] (1:1)	Freshwater - intermittent	0.0045 mg/l
	Marine sediment	0.033 mg/kg dry weight (d.w.)
	Fresh water sediment	0.328 mg/kg dry weight (d.w.)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version 9.0      Revision Date: 26.10.2023      SDS Number: 1330011-00046      Date of last issue: 07.05.2023  
Date of first issue: 27.02.2017

	Sewage treatment plant	10 mg/l
	Soil	0.065 mg/kg dry weight (d.w.)
	Fresh water	0.00045 mg/l
	Marine water	0.000045 mg/l
4,4'-(Hexafluoroisopropylidene)diphenol	Freshwater - intermittent	0.027 mg/l
	Fresh water	0.00522 mg/l
	Fresh water sediment	1.21 mg/kg dry weight (d.w.)
	Marine water - intermittent	0.027 mg/l
	Marine water	0.000522 mg/l
	Marine sediment	0.121 mg/kg dry weight (d.w.)
	Sewage treatment plant	4.787 mg/l
	Soil	0.239 mg/kg dry weight (d.w.)

### 8.2 Exposure controls

#### Engineering measures

Ensure adequate ventilation, especially in confined areas.  
Minimize workplace exposure concentrations.

#### Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:  
Chemical resistant goggles must be worn.  
Equipment should conform to I.S. EN 166

Hand protection  
Material : Nitrile rubber  
Glove thickness : 0.38 mm  
Wearing time : 480 min

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

Skin and body protection : Skin should be washed after contact.

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.  
Equipment should conform to I.S. EN 14387

Filter type : Combined particulates and acidic gas/vapour type (E-P)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2023
9.0	26.10.2023	1330011-00046	Date of first issue: 27.02.2017

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state	:	sheets
Colour	:	white, off-white
Odour	:	odourless
Odour Threshold	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
pH	:	No data available
Viscosity		
Viscosity, kinematic	:	Not applicable
Solubility(ies)		
Water solubility	:	insoluble



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2023
9.0	26.10.2023	1330011-00046	Date of first issue: 27.02.2017

---

Partition coefficient: n-octanol/water : Not applicable

Vapour pressure : Not applicable

Density : 1.75 - 1.90 g/cm<sup>3</sup>

Relative vapour density : Not applicable

Particle characteristics  
Particle size : No data available

### 9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : Not applicable

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Not classified as a reactivity hazard.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : None known.

### 10.4 Conditions to avoid

Conditions to avoid : None known.

### 10.5 Incompatible materials

Materials to avoid : None.

### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2023
9.0	26.10.2023	1330011-00046	Date of first issue: 27.02.2017

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Skin contact  
Ingestion  
Eye contact

##### Acute toxicity

Toxic by eye contact.

##### Product:

Acute oral toxicity	: Assessment: The substance or mixture has no acute oral toxicity
Acute inhalation toxicity	: Acute toxicity estimate: > 5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method
Acute dermal toxicity	: Assessment: The substance or mixture has no acute dermal toxicity

##### Components:

Reaction mass of 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]diphenol and benzyltriphenylphosphonium, salt with 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis[phenol] (1:1)

:

Acute oral toxicity	: LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 425 Assessment: The substance or mixture has no acute oral toxicity
---------------------	---

##### **4,4'-(Hexafluoroisopropylidene)diphenol:**

Acute oral toxicity	: LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 423 Assessment: The substance or mixture has no acute oral toxicity
Acute dermal toxicity	: LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 402 Assessment: The substance or mixture has no acute dermal toxicity

##### **Benzyltriphenylphosphonium chloride:**

Acute oral toxicity	: LD50 (Rat, male): 43 mg/kg
Acute inhalation toxicity	: LC50 (Rat, male): > 0.08 - 0.2 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2023
9.0	26.10.2023	1330011-00046	Date of first issue: 27.02.2017

---

Exposure time: 4 h  
Test atmosphere: dust/mist

### Skin corrosion/irritation

Not classified based on available information.

#### Components:

Reaction mass of 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]diphenol and benzyltriphenylphosphonium, salt with 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis[phenol] (1:1)

:

Species	:	Not tested on animals
Method	:	OECD Test Guideline 439
Result	:	No skin irritation

#### **4,4'-(Hexafluoroisopropylidene)diphenol:**

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	No skin irritation

#### **Benzyltriphenylphosphonium chloride:**

Species	:	Rabbit
Result	:	No skin irritation

### Serious eye damage/eye irritation

Not classified based on available information.

#### Product:

Result	:	No eye irritation
--------	---	-------------------

#### Components:

Reaction mass of 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]diphenol and benzyltriphenylphosphonium, salt with 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis[phenol] (1:1)

:

Species	:	In Vitro - Bovine
Method	:	OECD Test Guideline 437
Result	:	No eye irritation

#### **4,4'-(Hexafluoroisopropylidene)diphenol:**

Species	:	Rabbit
Method	:	OECD Test Guideline 405
Result	:	Irreversible effects on the eye

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2023
9.0	26.10.2023	1330011-00046	Date of first issue: 27.02.2017

### **Benzyltriphenylphosphonium chloride:**

Species	:	Rabbit
Result	:	Irreversible effects on the eye
Result	:	Toxic by eye contact.

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

Not classified based on available information.

#### **Respiratory sensitisation**

Not classified based on available information.

### **Components:**

Reaction mass of 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]diphenol and benzyltriphenylphosphonium, salt with 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis[phenol] (1:1)

:

Test Type	:	Direct Peptide Reactivity Assay (DPRA)
Exposure routes	:	Skin contact
Species	:	Not tested on animals
Method	:	OECD Test Guideline 442C
Result	:	equivocal

Test Type	:	KeratinoSens assay
Exposure routes	:	Skin contact
Species	:	Not tested on animals
Method	:	OECD Test Guideline 442D
Result	:	positive

Test Type	:	Maximisation Test
Exposure routes	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	negative
Remarks	:	Based on data from similar materials

Assessment	:	Does not cause skin sensitisation.
------------	---	------------------------------------

### **4,4'-(Hexafluoroisopropylidene)diphenol:**

Test Type	:	Maximisation Test
Exposure routes	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	negative

### **Benzyltriphenylphosphonium chloride:**

Test Type	:	Maximisation Test
-----------	---	-------------------

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2023
9.0	26.10.2023	1330011-00046	Date of first issue: 27.02.2017

Exposure routes : Skin contact  
Species : Guinea pig  
Result : negative

### Germ cell mutagenicity

Not classified based on available information.

### Components:

Reaction mass of 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]diphenol and benzyltriphenylphosphonium, salt with 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis[phenol] (1:1)

:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Germ cell mutagenicity- Assessment : Weight of evidence does not support classification as a germ cell mutagen.

### **4,4'-(Hexafluoroisopropylidene)diphenol:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OPPTS 870.5300  
Result: equivocal

### **Benzyltriphenylphosphonium chloride:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

### Carcinogenicity

Not classified based on available information.

### Reproductive toxicity

Not classified based on available information.

### Product:

Reproductive toxicity - Assessment : No toxicity to reproduction

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2023
9.0	26.10.2023	1330011-00046	Date of first issue: 27.02.2017

### Components:

Reaction mass of 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]diphenol and benzyltri-phenylphosphonium, salt with 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis[phenol] (1:1)

:

Effects on fertility	:	Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: Ingestion Method: OECD Test Guideline 422 Result: positive Remarks: Based on data from similar materials
Effects on foetal development	:	Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test Species: Rat Application Route: Ingestion Method: OECD Test Guideline 422 Result: negative Remarks: Based on data from similar materials
Reproductive toxicity - Assessment	:	Clear evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments

### **4,4'-(Hexafluoroisopropylidene)diphenol:**

Effects on fertility	:	Test Type: Reproduction/Developmental toxicity screening test Species: Rat Application Route: Ingestion Method: OECD Test Guideline 422 Result: positive
Effects on foetal development	:	Test Type: Reproduction/Developmental toxicity screening test Species: Rat Application Route: Ingestion Method: OECD Test Guideline 422 Result: negative
Reproductive toxicity - Assessment	:	Clear evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments

### **STOT - single exposure**

Not classified based on available information.

### Product:

Assessment	:	The substance or mixture is not classified as specific target organ toxicant, single exposure.
------------	---	--

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2023
9.0	26.10.2023	1330011-00046	Date of first issue: 27.02.2017

---

### Components:

#### **Benzyltriphenylphosphonium chloride:**

Assessment : May cause respiratory irritation.

#### **STOT - repeated exposure**

Not classified based on available information.

### Product:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

### Components:

Reaction mass of 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]diphenol and benzyltriphenylphosphonium, salt with 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis[phenol] (1:1)

:

Exposure routes	: Ingestion
Target Organs	: Seminal vesicle, Prostate
Assessment	: Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.

#### **4,4'-(Hexafluoroisopropylidene)diphenol:**

Exposure routes	: Ingestion
Target Organs	: Prostate, Seminal vesicle
Assessment	: Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.

#### **Benzyltriphenylphosphonium chloride:**

Exposure routes	: Inhalation
Target Organs	: Lungs, nasal cavity
Assessment	: Shown to produce significant health effects in animals at concentrations of 0.02 mg/l/6h/d or less.

### **Repeated dose toxicity**

### Components:

Reaction mass of 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]diphenol and benzyltriphenylphosphonium, salt with 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis[phenol] (1:1)

:

Species	: Rat, male and female
NOAEL	: 10 mg/kg
LOAEL	: 100 mg/kg
Application Route	: Ingestion

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2023
9.0	26.10.2023	1330011-00046	Date of first issue: 27.02.2017

Exposure time : 28 Days  
Method : OECD Test Guideline 407  
Remarks : Based on data from similar materials

### 4,4'-(Hexafluoroisopropylidene)diphenol:

Species : Rat, male and female  
NOAEL : 10 mg/kg  
LOAEL : 30 mg/kg  
Application Route : Ingestion  
Exposure time : 28 Days  
Method : OECD Test Guideline 407

### Benzyltriphenylphosphonium chloride:

Species : Rat, male  
NOAEL : 0.0051 mg/l  
LOAEL : 0.015 mg/l  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 2 Weeks

### Aspiration toxicity

Not classified based on available information.

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### Further information

#### Product:

Remarks : According to data on similar materials, and from modeling assessment, the product is not considered to require classification as dangerous to health.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product:

#### Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2023
9.0	26.10.2023	1330011-00046	Date of first issue: 27.02.2017

---

### Components:

Reaction mass of 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]diphenol and benzyltriphenylphosphonium, salt with 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis[phenol] (1:1)

:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 1.2 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 0.79 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	ErC50 (Raphidocelis subcapitata (freshwater green alga)): 0.45 mg/l Exposure time: 72 h Method: OECD Test Guideline 201  NOEC (Raphidocelis subcapitata (freshwater green alga)): 0.0087 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
M-Factor (Acute aquatic toxicity)	:	1
M-Factor (Chronic aquatic toxicity)	:	10

### **4,4'-(Hexafluoroisopropylidene)diphenol:**

Toxicity to fish	:	LC50 (Danio rerio (zebra fish)): 4.2 mg/l Exposure time: 48 h Method: OECD Test Guideline 215
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 2.7 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	ErC50 (Desmodesmus subspicatus (green algae)): 3 mg/l Exposure time: 72 h Method: OECD Test Guideline 201  NOEC (Pseudokirchneriella subcapitata (green algae)): 0.052 mg/l Exposure time: 3 d Method: OECD Test Guideline 201
Toxicity to fish (Chronic tox-)	:	NOEC: 0.125 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2023
9.0	26.10.2023	1330011-00046	Date of first issue: 27.02.2017

icity)  
Exposure time: 120 d  
Species: Danio rerio (zebra fish)  
Method: No data available

Toxicity to daphnia and other : NOEC: 0.23 mg/l  
aquatic invertebrates (Chronic toxicity) : Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211

M-Factor (Chronic aquatic toxicity) : 1

### **Benzyltriphenylphosphonium chloride:**

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1 mg/l  
aquatic invertebrates : Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata (green algae)): 0.59  
plants : mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
  
EC10 (Pseudokirchneriella subcapitata (green algae)): 0.25  
mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

## 12.2 Persistence and degradability

### **Components:**

Reaction mass of 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]diphenol and benzyltriphenylphosphonium, salt with 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis[phenol] (1:1)

:

Biodegradability : Result: Not readily biodegradable.  
Method: OECD Test Guideline 301B

### **4,4'-(Hexafluoroisopropylidene)diphenol:**

Biodegradability : Result: Not readily biodegradable.  
Method: OECD Test Guideline 301B

### **Benzyltriphenylphosphonium chloride:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2023
9.0	26.10.2023	1330011-00046	Date of first issue: 27.02.2017

---

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 1 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

### 12.3 Bioaccumulative potential

#### Components:

Reaction mass of 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]diphenol and benzyltriphenylphosphonium, salt with 4,4'-[2,2,2-trifluoro-1-(trifluoromethyl)ethylidene]bis[phenol] (1:1)

:

Partition coefficient: n-octanol/water : log Pow: 2.28

#### **4,4'-(Hexafluoroisopropylidene)diphenol:**

Bioaccumulation : Species: Zebrafish  
Bioconcentration factor (BCF): 9.8  
Method: OECD Test Guideline 305

Partition coefficient: n-octanol/water : log Pow: 2.79

#### **Benzyltriphenylphosphonium chloride:**

Partition coefficient: n-octanol/water : log Pow: -0.7  
Method: OECD Test Guideline 107

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2023
9.0	26.10.2023	1330011-00046	Date of first issue: 27.02.2017

### 12.7 Other adverse effects

No data available

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

- |                        |  |
|------------------------|--|
| Product                | : Dispose of in accordance with local regulations.<br>According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.<br>Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.<br>Do not dispose of waste into sewer. |
| Contaminated packaging | : Empty containers should be taken to an approved waste handling site for recycling or disposal.<br>If not otherwise specified: Dispose of as unused product.  |

## SECTION 14: Transport information

### 14.1 UN number or ID number

- |      |                                     |
|------|-------------------------------------|
| ADN  | : Not regulated as a dangerous good |
| ADR  | : Not regulated as a dangerous good |
| RID  | : Not regulated as a dangerous good |
| IMDG | : Not regulated as a dangerous good |
| IATA | : Not regulated as a dangerous good |

### 14.2 UN proper shipping name

- |      |                                     |
|------|-------------------------------------|
| ADN  | : Not regulated as a dangerous good |
| ADR  | : Not regulated as a dangerous good |
| RID  | : Not regulated as a dangerous good |
| IMDG | : Not regulated as a dangerous good |
| IATA | : Not regulated as a dangerous good |

### 14.3 Transport hazard class(es)

- |      |                                     |
|------|-------------------------------------|
| ADN  | : Not regulated as a dangerous good |
| ADR  | : Not regulated as a dangerous good |
| RID  | : Not regulated as a dangerous good |
| IMDG | : Not regulated as a dangerous good |
| IATA | : Not regulated as a dangerous good |

### 14.4 Packing group

- |     |                                     |
|-----|-------------------------------------|
| ADN | : Not regulated as a dangerous good |
|-----|-------------------------------------|

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2023
9.0	26.10.2023	1330011-00046	Date of first issue: 27.02.2017

<b>ADR</b>	: Not regulated as a dangerous good
<b>RID</b>	: Not regulated as a dangerous good
<b>IMDG</b>	: Not regulated as a dangerous good
<b>IATA (Cargo)</b>	: Not regulated as a dangerous good
<b>IATA (Passenger)</b>	: Not regulated as a dangerous good

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Not applicable

### 14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	: Conditions of restriction for the following entries should be considered: Number on list 75 If you intend to use this product as tattoo ink, please contact your vendor.  Cadmium (Number on list 75, 72, 28) Nickel (Number on list 75, 27)  Substance(s) or mixture(s) are listed here according to their appearance in the regulation, irrespective of their use/purpose or the conditions of the restriction. Please refer to the conditions in corresponding Regulation to determine whether an entry is applicable to the placing on the market or not.
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	: Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast)	: Not applicable
Regulation (EC) No 649/2012 of the European Parliament	: Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2023
9.0	26.10.2023	1330011-00046	Date of first issue: 27.02.2017

ment and the Council concerning the export and import  
of dangerous chemicals

REACH - List of substances subject to authorisation : Not applicable  
(Annex XIV)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of  
major-accident hazards involving dangerous substances.  
Not applicable

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

Other information : Viton™ and any associated logos are trademarks or copy-  
rights of The Chemours Company FC, LLC.  
Chemours™ and the Chemours Logo are trademarks of The  
Chemours Company.  
Before use read Chemours safety information.  
For further information contact the local Chemours office or  
nominated distributors.  
Do not use or resell Chemours™ materials in medical applica-  
tions involving implantation in the human body or contact with  
internal body fluids or tissues unless agreed to by Seller in a  
written agreement covering such use. For further information,  
please contact your Chemours representative.

Items where changes have been made to the previous version  
are highlighted in the body of this document by two vertical  
lines.

### Full text of H-Statements

H300	: Fatal if swallowed.
H318	: Causes serious eye damage.
H330	: Fatal if inhaled.
H335	: May cause respiratory irritation.
H360	: May damage fertility or the unborn child.
H372	: Causes damage to organs through prolonged or repeated exposure.
H373	: May cause damage to organs through prolonged or repeated exposure.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
EUH070	: Toxic by eye contact.

### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2023
9.0	26.10.2023	1330011-00046	Date of first issue: 27.02.2017

Repr.	: Reproductive toxicity
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

### Classification of the mixture:

Aquatic Chronic 3 H412

### Classification procedure:

Based on product data or assessment

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS mate-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2023
9.0	26.10.2023	1330011-00046	Date of first issue: 27.02.2017

---

Material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

IE / EN



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2023
9.0	26.10.2023	1330011-00046	Date of first issue: 27.02.2017

---

## Annex: Exposure Scenarios

### Table of Contents

Number	Title
ES1	Industrial use; Processing aid - Polymerisation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2023
9.0	26.10.2023	1330011-00046	Date of first issue: 27.02.2017

### ES 1: Industrial use; Processing aid - Polymerisation.

#### 1.1. Title section

<b>Exposure Scenario name</b>	: Use in rubber production and processing
<b>Structured Short Title</b>	: Industrial use; Processing aid - Polymerisation.

Environment		
<b>CS 1</b>	<b>Use in rubber production and processing</b>	ERC6d
Worker		
<b>CS 2</b>	<b>Use in polymer production, Mixing, Batch process</b>	PROC5
<b>CS 3</b>	<b>Material transfers, Non-dedicated facility</b>	PROC8a
<b>CS 4</b>	<b>Material transfers, Dedicated facility</b>	PROC8b
<b>CS 5</b>	<b>Pressing uncured rubber blanks, Curing chemical</b>	PROC14
<b>CS 6</b>	<b>Laboratory activities</b>	PROC15
<b>CS 7</b>	<b>Loading and unloading, Manual</b>	PROC21

#### 1.2. Conditions of use affecting exposure

##### 1.2.1. Control of environmental exposure: Use of reactive process regulators in polymerisation processes at industrial site (inclusion or not into/onto article) (ERC6d)

Product (article) characteristics	
Covers concentrations up to 4 %	
Physical form of product	: Solid, low dustiness
Amount used (or contained in articles), frequency and duration of use/exposure	
Annual amount per site	: 5 tonnes/year
Daily amount per site	: 23 kg/day
Emission days	: 220
<b>Release fraction to wastewater from process</b>	
Worst case assumption 0.02 %	
<b>Release fraction to air from process</b>	
Worst case assumption 0.1 %	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2023
9.0	26.10.2023	1330011-00046	Date of first issue: 27.02.2017

Technical and organisational conditions and measures	
Process designed to minimize releases to wastewater. Process designed to minimize releases to air. Soil emission controls are not applicable as there is no direct release to soil.	
Conditions and measures related to sewage treatment plant	
STP type	: Sewage treatment plant used
STP effluent	: 2,000 m3/d
Conditions and measures related to treatment of waste (including article waste)	
Waste treatment	: Contain and dispose of waste according to local regulations.
Other conditions affecting environmental exposure	
Receiving surface water flow	: 18,000 m3/d

### 1.2.2. Control of worker exposure: Mixing or blending in batch processes (PROC5)

Product (article) characteristics	
Covers concentrations up to 5 %	
Physical form of product	: Solid, low dustiness
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Local exhaust ventilation	
Assumes a good basic standard of occupational hygiene is implemented	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2023
9.0	26.10.2023	1330011-00046	Date of first issue: 27.02.2017

### 1.2.3. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Product (article) characteristics	
Covers concentrations up to 5 %	
Physical form of product	: Solid, low dustiness
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	
Assumes a good basic standard of occupational hygiene is implemented	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Dermal - minimum efficiency of 95 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use

### 1.2.4. Control of worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Product (article) characteristics	
Covers concentrations up to 5 %	
Physical form of product	: Solid, low dustiness
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Local exhaust ventilation	
Transfer via enclosed lines.	
Assumes a good basic standard of occupational hygiene is implemented	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2023
9.0	26.10.2023	1330011-00046	Date of first issue: 27.02.2017

Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use

### 1.2.5. Control of worker exposure: Tableting, compression, extrusion, pelettisation, granulation (PROC14)

Product (article) characteristics	
Covers concentrations up to 5 %	
Physical form of product	: Solid, low dustiness
Amount used (or contained in articles), frequency and duration of use/exposure	
Duration	: Covers daily exposures up to 8 hours
Technical and organisational conditions and measures	
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Local exhaust ventilation	
Assumes a good basic standard of occupational hygiene is implemented	
Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 90 %	
Other conditions affecting workers exposure	
Indoor or outdoor use	: Indoor use

### 1.2.6. Control of worker exposure: Use as laboratory reagent (PROC15)

Product (article) characteristics	
Covers concentrations up to 5 %	
Physical form of product	: Solid, low dustiness
Amount used (or contained in articles), frequency and duration of use/exposure	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version 9.0	Revision Date: 26.10.2023	SDS Number: 1330011-00046	Date of last issue: 07.05.2023 Date of first issue: 27.02.2017
----------------	------------------------------	------------------------------	---

Duration	: Covers daily exposures up to 8 hours
<b>Technical and organisational conditions and measures</b>	
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).	
Assumes a good basic standard of occupational hygiene is implemented	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 90 %	
<b>Other conditions affecting workers exposure</b>	
Indoor or outdoor use	: Indoor use

### 1.2.7. Control of worker exposure: Low energy manipulation and handling of substances bound in/on materials and/or articles (PROC21)

<b>Product (article) characteristics</b>	
Covers concentrations up to 1 %	
Physical form of product	: Solid, low dustiness
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Covers daily exposures up to 8 hours
<b>Technical and organisational conditions and measures</b>	
Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Local exhaust ventilation	
Assumes a good basic standard of occupational hygiene is implemented	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 90 %	
<b>Other conditions affecting workers exposure</b>	
Indoor or outdoor use	: Indoor use

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version 9.0      Revision Date: 26.10.2023      SDS Number: 1330011-00046      Date of last issue: 07.05.2023  
Date of first issue: 27.02.2017

### 1.3. Exposure estimation and reference to its source

#### 1.3.1. Environmental release and exposure: Use of reactive process regulators in polymerisation processes at industrial site (inclusion or not into/onto article) (ERC6d)

Protection Target	Exposure estimate	RCR
Freshwater	0.0012 mg/L (ECETOC TRA)	0.3
Freshwater sediment	0.09 mg/kg dry weight (ECETOC TRA)	0.3
Marine water	0.000023 mg/L (ECETOC TRA)	0.5
Marine sediment	0.017 mg/kg dry weight (ECETOC TRA)	0.5
Sewage treatment plant	0.0012 mg/L (ECETOC TRA)	< 0.001
Agricultural soil	0.045 mg/kg dry weight (ECETOC TRA)	0.7
Man via environment - Oral	0.000086 mg/kg bw/day (ECETOC TRA)	0.002

#### 1.3.2. Worker exposure: Mixing or blending in batch processes (PROC5)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.007 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0.06
dermal	systemic	long-term	0.03 mg/kg bw/day (ECETOC TRA worker v3)	0.83

#### 1.3.3. Worker exposure: Transfer of substance or mixture (charging/discharging) at non dedicated-facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	< 0.007 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0.058
dermal	systemic	long-term	0.013 mg/kg bw/day (ECETOC TRA worker v3)	0.39

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version 9.0      Revision Date: 26.10.2023      SDS Number: 1330011-00046      Date of last issue: 07.05.2023  
Date of first issue: 27.02.2017

### 1.3.4. Worker exposure: Transfer of substance or mixture (charging/discharging) at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.001 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0.008
dermal	systemic	long-term	< 0.002 mg/kg bw/day (ECETOC TRA worker v3)	0.039

### 1.3.5. Worker exposure: Tableting, compression, extrusion, pelettisation, granulation (PROC14)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.002 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0.017
dermal	systemic	long-term	0.007 mg/kg bw/day (ECETOC TRA worker v3)	0.21

### 1.3.6. Worker exposure: Use as laboratory reagent (PROC15)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.014 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0.12
dermal	systemic	long-term	0.007 mg/kg bw/day (ECETOC TRA worker v3)	0.21

### 1.3.7. Worker exposure: Low energy manipulation and handling of substances bound in/on materials and/or articles (PROC21)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.01 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0.08
dermal	systemic	long-term	0.03 mg/kg bw/day (ECETOC TRA)	0.86



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by  
Commission Regulation (EU) 2020/878



## Viton™ VTR-9208 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 07.05.2023
9.0	26.10.2023	1330011-00046	Date of first issue: 27.02.2017

			worker v3)	
--	--	--	------------	--

### 1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

For further information, please contact [sds-support@chemours.com](mailto:sds-support@chemours.com).