

SAFETY DATA SHEET



DryFilm RA/IPA

Version	Revision Date:	SDS Number:	Date of last issue:
3.2	01.11.2023	1328660-00033	16.03.2023
			Date of first issue: 27.02.2017

SECTION 1: IDENTIFICATION

Product name : DryFilm RA/IPA

SDS-Identcode : 130000001461

Manufacturer or supplier's details

Company : The Chemours Company (Australia) Pty Ltd (C/O Ashurst Australia)

Address : Level 26, 181 William Street
Melbourne VIC 3000 Australia

Telephone : 1300 915 623

Emergency telephone number : Medical emergency: 1800 674 415 (24 h) ; Transport emergency: +61 2 9037 2994

Recommended use of the chemical and restrictions on use

Recommended use : Dry lubricant

Restrictions on use : For industrial use only.
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

SECTION 2. HAZARDS IDENTIFICATION



GHS Classification

Flammable liquids : Category 2

Serious eye damage/eye irritation : Category 2A

Specific target organ toxicity - single exposure : Category 3

GHS label elements

Hazard pictograms :  

Signal word : Danger

SAFETY DATA SHEET



DryFilm RA/PA

Version	Revision Date:	SDS Number:	Date of last issue: 16.03.2023
3.2	01.11.2023	1328660-00033	Date of first issue: 27.02.2017

Hazard statements : H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P261 Avoid breathing mist or vapours.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice/ attention.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

The thermal decomposition vapours of fluorinated plastics may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco.
Vapours may form explosive mixture with air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Propan-2-ol	67-63-0	>= 60 -<= 100

SAFETY DATA SHEET



DryFilm RA/IPA

Version 3.2	Revision Date: 01.11.2023	SDS Number: 1328660-00033	Date of last issue: 16.03.2023 Date of first issue: 27.02.2017
----------------	------------------------------	------------------------------	---

SECTION 4. FIRST AID MEASURES

- | | |
|---|--|
| General advice | : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice. |
| If inhaled | : If inhaled, remove to fresh air.
Get medical attention if symptoms occur. |
| In case of skin contact | : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention if symptoms occur. |
| In case of eye contact | : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention. |
| If swallowed | : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water. |
| Most important symptoms and effects, both acute and delayed | : Inhalation may provoke the following symptoms:
Polymer fume fever
Eye contact may provoke the following symptoms
Irritation
Causes serious eye irritation.
May cause drowsiness or dizziness. |
| Protection of first-aiders | : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8). |
| Notes to physician | : Treat symptomatically and supportively. |

SECTION 5. FIREFIGHTING MEASURES

- | | |
|---------------------------------------|--|
| Suitable extinguishing media | : Water spray
Alcohol-resistant foam
Carbon dioxide (CO ₂)
Dry chemical |
| Unsuitable extinguishing media | : High volume water jet |
| Specific hazards during fire-fighting | : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapours may form explosive mixtures with air. |

SAFETY DATA SHEET



DryFilm RA/IPA

Version	Revision Date:	SDS Number:	Date of last issue: 16.03.2023
3.2	01.11.2023	1328660-00033	Date of first issue: 27.02.2017

Exposure to combustion products may be a hazard to health.

- Hazardous combustion products : Carbon oxides
Hydrogen fluoride
carbonyl fluoride
potentially toxic fluorinated compounds
aerosolized particulates
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
- Hazchem Code : •2YE
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Ventilate the area.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

DryFilm RA/IPA

Version	Revision Date:	SDS Number:	Date of last issue:
3.2	01.11.2023	1328660-00033	16.03.2023
			Date of first issue: 27.02.2017

SECTION 7. HANDLING AND STORAGE

- | | | |
|-----------------------------|---|---|
| Technical measures | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : | If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment. |
| Advice on safe handling | : | Avoid breathing mist or vapours.
Do not swallow.
Do not get in eyes.
Avoid prolonged or repeated contact with skin.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Non-sparking tools should be used.
Keep container tightly closed.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.

Do not breathe decomposition products. |
| Hygiene measures | : | If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use. |
| Conditions for safe storage | : | Keep in properly labelled containers.
Store locked up.
Keep tightly closed.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Keep away from heat and sources of ignition. |
| Materials to avoid | : | Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable gases
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Poisonous gases
Explosives |

SAFETY DATA SHEET



DryFilm RA/PA

Version 3.2 Revision Date: 01.11.2023 SDS Number: 1328660-00033 Date of last issue: 16.03.2023
Date of first issue: 27.02.2017

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Propan-2-ol	67-63-0	STEL	500 ppm 1,230 mg/m ³	AU OEL
		TWA	400 ppm 983 mg/m ³	AU OEL
		TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
hydrofluoric acid	7664-39-3	Peak limit	3 ppm 2.6 mg/m ³ (Fluorine)	AU OEL
		TWA	0.5 ppm (Fluorine)	ACGIH
		C	2 ppm (Fluorine)	ACGIH
Carbonyl difluoride	353-50-4	TWA	2 ppm 5.4 mg/m ³	AU OEL
		STEL	5 ppm 13 mg/m ³	AU OEL
		TWA	2 ppm	ACGIH
		STEL	5 ppm	ACGIH
Carbon dioxide	124-38-9	TWA	5,000 ppm 9,000 mg/m ³	AU OEL
		STEL	30,000 ppm 54,000 mg/m ³	AU OEL
		TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
Carbon monoxide	630-08-0	TWA	30 ppm 34 mg/m ³	AU OEL
		TWA	25 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of work-week	40 mg/l	ACGIH BEI

SAFETY DATA SHEET



DryFilm RA/PA

Version	Revision Date:	SDS Number:	Date of last issue: 16.03.2023
3.2	01.11.2023	1328660-00033	Date of first issue: 27.02.2017

Engineering measures : Processing may form hazardous compounds (see section 10).
Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.
Use explosion-proof electrical, ventilating and lighting equipment.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates, acidic gas/vapour and organic vapour type

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Take note that the product is flammable, which may impact the selection of hand protection. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : translucent, white to off-white

SAFETY DATA SHEET



DryFilm RA/PA

Version	Revision Date:	SDS Number:	Date of last issue: 16.03.2023
3.2	01.11.2023	1328660-00033	Date of first issue: 27.02.2017

Odour	: alcohol-like
Odour Threshold	: No data available
pH	: 4 - 7
Melting point/freezing point	: -89 °C
Initial boiling point and boiling range	: 82 °C
Flash point	: 12 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: Not applicable
Flammability (liquids)	: Ignitable (see flash point)
Upper explosion limit / Upper flammability limit	: 12.0 %(V)
Lower explosion limit / Lower flammability limit	: 2.0 %(V)
Vapour pressure	: 44 hPa (20 °C)
Relative vapour density	: 2.07 (Air = 1.0)
Relative density	: 0.96 (22 °C)
Solubility(ies)	
Water solubility	: partly soluble
Partition coefficient: n-octanol/water	: Not applicable
Auto-ignition temperature	: 399 °C
Decomposition temperature	: 300 °C
Viscosity	
Viscosity, kinematic	: No data available
Explosive properties	: Not explosive

SAFETY DATA SHEET



DryFilm RA/PA

Version	Revision Date:	SDS Number:	Date of last issue: 16.03.2023
3.2	01.11.2023	1328660-00033	Date of first issue: 27.02.2017

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Highly flammable liquid and vapour.
Vapours may form explosive mixture with air.
Can react with strong oxidizing agents.
Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products

Thermal decomposition : hydrofluoric acid
Carbonyl difluoride
Carbon dioxide
Carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

Exposure routes : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Propan-2-ol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25 mg/l
Exposure time: 6 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

DryFilm RA/IPA

Version	Revision Date:	SDS Number:	Date of last issue: 16.03.2023
3.2	01.11.2023	1328660-00033	Date of first issue: 27.02.2017

Skin corrosion/irritation

Not classified based on available information.

Components:**Propan-2-ol:**

Species	:	Rabbit
Result	:	No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:**Propan-2-ol:**

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:**Propan-2-ol:**

Test Type	:	Buehler Test
Exposure routes	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	negative

Chronic toxicity**Germ cell mutagenicity**

Not classified based on available information.

Components:**Propan-2-ol:**

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Result: negative
		Test Type: In vitro mammalian cell gene mutation test Result: negative
Genotoxicity in vivo	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse

SAFETY DATA SHEET



DryFilm RA/PA

Version	Revision Date:	SDS Number:	Date of last issue: 16.03.2023
3.2	01.11.2023	1328660-00033	Date of first issue: 27.02.2017

Application Route: Intraperitoneal injection
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Propan-2-ol:

Species	: Rat
Application Route	: inhalation (vapour)
Exposure time	: 104 weeks
Method	: OECD Test Guideline 451
Result	: negative

Reproductive toxicity

Not classified based on available information.

Components:

Propan-2-ol:

Effects on fertility	: Test Type: Two-generation reproduction toxicity study Species: Rat Application Route: Ingestion Result: negative
----------------------	---

Effects on foetal development	: Test Type: Embryo-foetal development Species: Rat Application Route: Ingestion Result: negative
-------------------------------	--

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Propan-2-ol:

Assessment	: May cause drowsiness or dizziness.
------------	--------------------------------------

STOT - repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Propan-2-ol:

Species	: Rat
NOAEL	: 12.5 mg/l
Application Route	: inhalation (vapour)
Exposure time	: 104 Weeks

SAFETY DATA SHEET



DryFilm RA/PA

Version 3.2	Revision Date: 01.11.2023	SDS Number: 1328660-00033	Date of last issue: 16.03.2023 Date of first issue: 27.02.2017
----------------	------------------------------	------------------------------	---

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Propan-2-ol:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 9,640 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 24 h
Toxicity to microorganisms	:	EC50 (Pseudomonas putida): > 1,050 mg/l Exposure time: 16 h

Persistence and degradability

Components:

Propan-2-ol:

Biodegradability	:	Result: rapidly degradable
BOD/COD	:	BOD: 1.19 (BOD5)COD: 2.23BOD/COD: 53 %

Bioaccumulative potential

Components:

Propan-2-ol:

Partition coefficient: n-octanol/water	:	log Pow: 0.05
--	---	---------------

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	:	Do not dispose of waste into sewer. Dispose of in accordance with local regulations.
---------------------	---	---

SAFETY DATA SHEET



DryFilm RA/PA

Version	Revision Date:	SDS Number:	Date of last issue: 16.03.2023
3.2	01.11.2023	1328660-00033	Date of first issue: 27.02.2017

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number	: UN 1219
Proper shipping name	: ISOPROPANOL SOLUTION
Class	: 3
Packing group	: II
Labels	: 3
Environmentally hazardous	: no

IATA-DGR

UN/ID No.	: UN 1219
Proper shipping name	: Isopropanol solution
Class	: 3
Packing group	: II
Labels	: Flammable Liquids
Packing instruction (cargo aircraft)	: 364
Packing instruction (passenger aircraft)	: 353

IMDG-Code

UN number	: UN 1219
Proper shipping name	: ISOPROPANOL SOLUTION
Class	: 3
Packing group	: II
Labels	: 3
EmS Code	: F-E, S-D
Marine pollutant	: no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

UN number	: UN 1219
Proper shipping name	: ISOPROPANOL SOLUTION
Class	: 3
Packing group	: II
Labels	: 3
Hazchem Code	: •2YE

SAFETY DATA SHEET



DryFilm RA/IPA

Version	Revision Date:	SDS Number:	Date of last issue: 16.03.2023
3.2	01.11.2023	1328660-00033	Date of first issue: 27.02.2017

Environmentally hazardous : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibition/Licensing Requirements	: There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regulations.
------------------------------------	---

SECTION 16: ANY OTHER RELEVANT INFORMATION

Other information	: Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information. For further information contact the local Chemours office or nominated distributors.
-------------------	---

Further information

Revision Date	: 01.11.2023
---------------	--------------

Sources of key data used to compile the Safety Data Sheet	: Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, http://echa.europa.eu/
---	---

Date format	: dd.mm.yyyy
-------------	--------------

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
AU OEL	: Australia. Workplace Exposure Standards for Airborne Contaminants.

ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
ACGIH / C	: Ceiling limit
AU OEL / TWA	: Exposure standard - time weighted average
AU OEL / STEL	: Exposure standard - short term exposure limit
AU OEL / Peak limit	: Exposure standard - peak

SAFETY DATA SHEET



DryFilm RA/PA

Version	Revision Date:	SDS Number:	Date of last issue: 16.03.2023
3.2	01.11.2023	1328660-00033	Date of first issue: 27.02.2017

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

AU / EN