

SAFETY DATA SHEET



Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 18.10.2022
4.1	14.04.2023	1354346-00045	Date of first issue: 27.02.2017

SECTION 1: Identification of the hazardous chemical and of the supplier

Product identifier

Product name : Opteon™ XP30 (R-514A) Refrigerant

Chemical name :

CAS-No. : Not Assigned

Product code :

SDS-Identcode : 130000143454

Recommended use of the chemical and restrictions on use

Recommended use : Refrigerant
Heat transfer fluids

Restrictions on use : For professional and industrial installation and use only.
Do not use product for anything outside of the above specified uses

Manufacturer or supplier's details

Company : The Chemours Malaysia Sdn. Bhd.

Address : Suite 20-01 & 20-02B, Level 20, The Pinnacle, Persiaran Lagoon, Bandar Sunway, Subang Jaya
Selangor Darul Ehsan 47500 Malaysia

Telephone : +60 3 5021 0178

Emergency telephone number : 1-800-815-308

Telefax : +60 3 2178 4719

SECTION 2: Hazards identification

Classification of the hazardous chemical

Serious eye damage/eye irritation : Category 2

Specific target organ toxicity - single exposure : Category 3

Hazardous to the aquatic environment - chronic hazard : Category 3


Label elements

SAFETY DATA SHEET



Opteon™ XP30 (R-514A) Refrigerant

Version 4.1 Revision Date: 14.04.2023 SDS Number: 1354346-00045 Date of last issue: 18.10.2022
Date of first issue: 27.02.2017

Hazard pictograms : 

Signal word : Warning

Hazard statements : H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear eye protection/ face protection.

Response:
P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice/ attention.

Storage:
P405 Store locked up.

Other hazards which do not result in classification

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.

Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.

Rapid evaporation of the product may cause frostbite.

SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
(Z)-1,1,1,4,4,4-Hexafluoro-2-butene#	692-49-9	74.7
Trans-Dichloroethylene	156-60-5	25.3

Voluntarily-disclosed substance

SECTION 4: First aid measures

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical

SAFETY DATA SHEET



Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 18.10.2022
4.1	14.04.2023	1354346-00045	Date of first issue: 27.02.2017

- advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water
for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : May cause cardiac arrhythmia.
Other symptoms potentially related to misuse or inhalation abuse are
Cardiac sensitisation
Anaesthetic effects
Light-headedness
Dizziness
confusion
Lack of coordination
Drowsiness
Unconsciousness
Skin contact may provoke the following symptoms:
Irritation
Swelling of tissue
Itching
Discomfort
Redness
Eye contact may provoke the following symptoms
tearing
Redness
Discomfort
Causes serious eye irritation.
May cause drowsiness or dizziness.
- Protection of first-aiders : First Aid responders should pay attention to self-protection,
and use the recommended personal protective equipment
when the potential for exposure exists (see section 8).
- Notes to physician : Because of possible disturbances of cardiac rhythm, cate-
cholamine drugs, such as epinephrine, that may be used in
situations of emergency life support should be used with spe-
cial caution.

Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 18.10.2022
4.1	14.04.2023	1354346-00045	Date of first issue: 27.02.2017

SECTION 5: Firefighting measures**Extinguishing media**

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

Physicochemical hazards arising from the chemical

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Hydrogen fluoride
carbonyl fluoride
Carbon oxides
Chlorine compounds

Special protective equipment and precautions for fire-fighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and dis-

SAFETY DATA SHEET



Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 18.10.2022
4.1	14.04.2023	1354346-00045	Date of first issue: 27.02.2017

posal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7: Handling and storage

Handling

Precautions for safe handling

- | | | |
|-------------------------|---|--|
| Technical measures | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : | If sufficient ventilation is unavailable, use with local exhaust ventilation. |
| Advice on safe handling | : | <p>Do not get on skin or clothing.</p> <p>Avoid breathing mist or vapours.</p> <p>Do not swallow.</p> <p>Do not get in eyes.</p> <p>Wash skin thoroughly after handling.</p> <p>Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment</p> <p>Valve protection caps and valve outlet threaded plugs must remain in place unless container is secured with valve outlet piped to use point.</p> <p>Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder.</p> <p>Use a pressure reducing regulator when connecting cylinder to lower pressure (<3000 psig) piping or systems.</p> <p>Never attempt to lift cylinder by its cap.</p> <p>Do not drag, slide or roll cylinders.</p> <p>Use a suitable hand truck for cylinder movement.</p> <p>Take care to prevent spills, waste and minimize release to the environment.</p> |

Storage

Conditions for safe storage, including any incompatibilities

- | | | |
|-----------------------------|---|--|
| Conditions for safe storage | : | <p>Cylinders should be stored upright and firmly secured to prevent falling or being knocked over.</p> <p>Separate full containers from empty containers.</p> <p>Do not store near combustible materials.</p> <p>Avoid area where salt or other corrosive materials are present.</p> <p>Do not expose drums to direct heat or temperature above 46°C (115°F) to avoid pressurizing and possibly distorting the drums.</p> <p>Material should not be dispensed by pouring from pail/drum shipping containers containing 5 gallons or more. The use of a drum pump is recommended for dispensing from pail/drum shipping containers with 5 gallons or more, except for smaller</p> |
|-----------------------------|---|--|

SAFETY DATA SHEET



Opteon™ XP30 (R-514A) Refrigerant

Version 4.1 Revision Date: 14.04.2023 SDS Number: 1354346-00045 Date of last issue: 18.10.2022
Date of first issue: 27.02.2017

containers where adequate ventilation can be used to manage the exposure.
Keep in properly labelled containers.
Store locked up.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.

Materials to avoid : No special restrictions on storage with other products.

Recommended storage temperature : < 46 °C

Storage period : > 10 yr

Further information on storage stability : The product has an indefinite shelf life when stored properly.

Keep away from direct sunlight.

SECTION 8: Exposure controls and personal protection

Control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Trans-Dichloroethylene	156-60-5	TWA	200 ppm	ACGIH

Appropriate engineering controls : Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.

Individual protection measures, such as personal protective equipment

Eye/face protection : Wear the following personal protective equipment:
Safety goggles

Skin protection : Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.

Hand protection
Material : Heat resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

SAFETY DATA SHEET



Opteon™ XP30 (R-514A) Refrigerant

Version 4.1	Revision Date: 14.04.2023	SDS Number: 1354346-00045	Date of last issue: 18.10.2022 Date of first issue: 27.02.2017
----------------	------------------------------	------------------------------	---

Respiratory protection	: If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
Filter type	: Organic gas and low boiling vapour type
Hygiene measures	: If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

SECTION 9: Physical and chemical properties

Appearance	: liquid
Colour	: clear
Odour	: slight, ether-like
Odour Threshold	: No data available
pH	: 7
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: 29.1 °C
Flash point	: Method: ASTM D 56 does not flash
Evaporation rate	: No data available
Flammability (solid, gas)	: Not applicable
Flammability (liquids)	: No data available
Upper explosion limit / Upper flammability limit	: Upper flammability limit Method: ASTM E681 None.
Lower explosion limit / Lower flammability limit	: Lower flammability limit Method: ASTM E681 None.
Vapour pressure	: 871.4 hPa (25 °C)

SAFETY DATA SHEET



Opteon™ XP30 (R-514A) Refrigerant

Version 4.1	Revision Date: 14.04.2023	SDS Number: 1354346-00045	Date of last issue: 18.10.2022 Date of first issue: 27.02.2017
----------------	------------------------------	------------------------------	---

Relative vapour density	: 5.01 (Air = 1.0)
Relative density	: 1.31 (25 °C)
Density	: 1.308 g/cm ³ (25 °C)
Solubility(ies) Water solubility	: No data available
Partition coefficient: n-octanol/water	: Not applicable
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity Viscosity, kinematic	: No data available
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Particle size	: Not applicable

SECTION 10: Stability and reactivity

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: None known.
Conditions to avoid	: None known.
Incompatible materials	: None.
Hazardous decomposition products	: No hazardous decomposition products are known.

SECTION 11: Toxicological information

Information on likely routes of exposure	: Inhalation Skin contact Ingestion Eye contact
--	--

Acute toxicity

Not classified based on available information.

SAFETY DATA SHEET



Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 18.10.2022
4.1	14.04.2023	1354346-00045	Date of first issue: 27.02.2017

Components:

(Z)-1,1,1,4,4,4-Hexafluoro-2-butene:

Acute inhalation toxicity : LC50 (Rat): > 690.413 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

No observed adverse effect concentration (Dog): 12500 ppm
Test atmosphere: gas

Lowest observed adverse effect concentration (Dog): 25000 ppm
Test atmosphere: gas

Cardiac sensitisation threshold limit (Dog): 1,677,740 mg/m3
Test atmosphere: gas

Trans-Dichloroethylene:

Acute oral toxicity : LD50 (Rat): 7,902 mg/kg
Method: OECD Test Guideline 420

Acute inhalation toxicity : LC50 (Rat): 95.5 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

Lowest observed adverse effect concentration (Dog): 250000 ppm
Test atmosphere: gas

Cardiac sensitisation threshold limit (Dog): 991,309 mg/m3
Test atmosphere: gas

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Components:

(Z)-1,1,1,4,4,4-Hexafluoro-2-butene:

Result : No skin irritation

Trans-Dichloroethylene:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Mild skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 18.10.2022
4.1	14.04.2023	1354346-00045	Date of first issue: 27.02.2017

Components:**(Z)-1,1,1,4,4,4-Hexafluoro-2-butene:**

Result : No eye irritation

Trans-Dichloroethylene:

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 7 days
Method	:	OECD Test Guideline 405

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:**(Z)-1,1,1,4,4,4-Hexafluoro-2-butene:**

Exposure routes	:	Skin contact
Result	:	negative

Germ cell mutagenicity

Not classified based on available information.

Components:**(Z)-1,1,1,4,4,4-Hexafluoro-2-butene:**

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
-----------------------	---	---

	:	Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative
--	---	---

	:	Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative
--	---	--

Genotoxicity in vivo	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: inhalation (vapour) Method: OECD Test Guideline 474 Result: negative
----------------------	---	---

Germ cell mutagenicity - Assessment	:	Weight of evidence does not support classification as a germ cell mutagen.
-------------------------------------	---	--

Trans-Dichloroethylene:

SAFETY DATA SHEET



Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 18.10.2022
4.1	14.04.2023	1354346-00045	Date of first issue: 27.02.2017

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
- Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
- Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
- Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative
- Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

Components:

(Z)-1,1,1,4,4,4-Hexafluoro-2-butene:

- Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 416
Result: negative
- Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 414
Result: negative
- Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity, No effects on or via lactation

Trans-Dichloroethylene:

- Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Inhalation
Method: OECD Test Guideline 414
Result: negative

SAFETY DATA SHEET



Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 18.10.2022
4.1	14.04.2023	1354346-00045	Date of first issue: 27.02.2017

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Trans-Dichloroethylene:

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Components:

(Z)-1,1,1,4,4,4-Hexafluoro-2-butene:

Exposure routes : inhalation (vapour)
Assessment : No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or less.

Trans-Dichloroethylene:

Exposure routes : Inhalation
Assessment : No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less.

Exposure routes : Ingestion
Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Repeated dose toxicity

Components:

(Z)-1,1,1,4,4,4-Hexafluoro-2-butene:

Species : Rat, male and female
NOAEL : 33.5 mg/l
LOAEL : 50.3 mg/l
Application Route : inhalation (vapour)
Exposure time : 90 d
Method : OECD Test Guideline 413

Trans-Dichloroethylene:

Species : Rat, male and female
NOAEL : 4000 ppm
LOAEL : > 4000 ppm
Application Route : Inhalation
Exposure time : 90 Days
Method : OECD Test Guideline 413

Species : Rat, male and female
NOAEL : 3,210 mg/kg
LOAEL : > 3,210 mg/kg
Application Route : Ingestion
Exposure time : 98 Days
Method : OECD Test Guideline 408

Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 18.10.2022
4.1	14.04.2023	1354346-00045	Date of first issue: 27.02.2017

Aspiration toxicity

Not classified based on available information.

Components:**(Z)-1,1,1,4,4,4-Hexafluoro-2-butene:**

No aspiration toxicity classification

SECTION 12: Ecological information**Ecotoxicity****Components:****(Z)-1,1,1,4,4,4-Hexafluoro-2-butene:**

- | | | |
|--|---|---|
| Toxicity to fish | : | LC50 (<i>Oryzias latipes</i> (Japanese medaka)): 76.1 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203 |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (<i>Daphnia magna</i> (Water flea)): 22.5 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202 |
| Toxicity to algae/aquatic plants | : | ErC50 (<i>Pseudokirchneriella subcapitata</i> (green algae)): > 23.7 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (<i>Pseudokirchneriella subcapitata</i> (green algae)): 6.92 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201 |
| Toxicity to fish (Chronic toxicity) | : | NOEC (<i>Gobiocypris rarus</i> (rare gudgeon)): 10 mg/l
Exposure time: 32 d
Method: OECD Test Guideline 210 |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : | NOEC (<i>Daphnia magna</i> (Water flea)): 10 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211 |

Trans-Dichloroethylene:

- | | | |
|---|---|---|
| Toxicity to fish | : | LC50 (<i>Lepomis macrochirus</i> (Bluegill sunfish)): 135 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (<i>Daphnia magna</i> (Water flea)): 220 mg/l
Exposure time: 48 h
Method: EPA-660/3-75-009 |
| Toxicity to algae/aquatic plants | : | EbC50 (<i>Pseudokirchneriella subcapitata</i> (green algae)): 36.36 mg/l |

SAFETY DATA SHEET



Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 18.10.2022
4.1	14.04.2023	1354346-00045	Date of first issue: 27.02.2017

Exposure time: 48 h
Method: OECD Test Guideline 201

Persistence and degradability

Components:

(Z)-1,1,1,4,4,4-Hexafluoro-2-butene:

Biodegradability : Result: Not readily biodegradable.
Method: OECD Test Guideline 302C

Trans-Dichloroethylene:

Biodegradability : Result: not rapidly degradable
Method: OECD Test Guideline 301D

Bioaccumulative potential

Components:

(Z)-1,1,1,4,4,4-Hexafluoro-2-butene:

Partition coefficient: n-octanol/water : log Pow: 2.3

Trans-Dichloroethylene:

Partition coefficient: n-octanol/water : log Pow: 2.06

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13: Disposal information

Disposal methods

Waste from residues : Disposal of waste to be in accordance with the Environmental Quality (Scheduled Wastes) Regulations and other guidelines issuance by DOE and/or local authorities.
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14: Transport information

International Regulations

UNRTDG

UN number : Not applicable

SAFETY DATA SHEET



Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 18.10.2022
4.1	14.04.2023	1354346-00045	Date of first issue: 27.02.2017

Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable

IATA-DGR

UN/ID No. : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Packing instruction (cargo aircraft) : Not applicable
Packing instruction (passenger aircraft) : Not applicable

IMDG-Code

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
EmS Code : Not applicable
Marine pollutant : Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

Not applicable

SECTION 15: Regulatory information

Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

SECTION 16: Other information

Revision Date : 14.04.2023

Other information : Opteon™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.
Chemours™ and the Chemours Logo are trademarks of The Chemours Company.
Before use read Chemours safety information.
For further information contact the local Chemours office or nominated distributors.

Further information

SAFETY DATA SHEET



Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 18.10.2022
4.1	14.04.2023	1354346-00045	Date of first issue: 27.02.2017

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIH / TWA : 8-hour, time-weighted average

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

MY / EN