

# SAFETY DATA SHEET



## Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 14.04.2023
6.1	27.06.2023	1354329-00049	Date of first issue: 27.02.2017

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Opteon™ XP30 (R-514A) Refrigerant

SDS-Identcode : 130000143454

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Refrigerant, Heat transfer fluids

Recommended restrictions  
on use : For professional and industrial installation and use only., Do  
not use product for anything outside of the above specified  
uses

#### 1.3 Details of the supplier of the safety data sheet

Company : Chemours Netherlands B.V.  
Baanhoekweg 22  
3313 LA Dordrecht Netherlands

Telephone : +31-(0)-78-630-1011

Telefax : +31-78-6163737

E-mail address of person  
responsible for the SDS : sds-support@chemours.com

#### 1.4 Emergency telephone number

+(44)-870-8200418 (CHEMTREC - Recommended)

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single ex-  
posure, Category 3 H336: May cause drowsiness or dizziness.

Long-term (chronic) aquatic hazard, Cat-  
egory 3 H412: Harmful to aquatic life with long lasting ef-  
fects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

# SAFETY DATA SHEET



## Opteon™ XP30 (R-514A) Refrigerant

Version 6.1      Revision Date: 27.06.2023      SDS Number: 1354329-00049      Date of last issue: 14.04.2023  
Date of first issue: 27.02.2017

Hazard pictograms :



Signal word : Warning

Hazard statements :  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements :  
**Prevention:**  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P280 Wear eye protection/ face protection.  
**Response:**  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.

Hazardous components which must be listed on the label:

Trans-Dichloroethylene

### Additional Labelling

EUH205 Contains epoxy constituents. May produce an allergic reaction.  
EUH209 Can become highly flammable in use.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.

Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.

Rapid evaporation of the product may cause frostbite.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
(Z)-1,1,1,4,4,4-Hexafluoro-2-butene#	692-49-9		74,7

# SAFETY DATA SHEET



## Opteon™ XP30 (R-514A) Refrigerant

Version 6.1      Revision Date: 27.06.2023      SDS Number: 1354329-00049      Date of last issue: 14.04.2023  
Date of first issue: 27.02.2017

	01-2119929623-35		
Trans-Dichloroethylene	156-60-5 205-860-2 602-026-00-3 01-2120093504-55	Flam. Liq. 2; H225 Acute Tox. 4; H332 Eye Irrit. 2; H319 STOT SE 3; H336 Aquatic Chronic 3; H412	25,3

For explanation of abbreviations see section 16.  
#: Voluntarily-disclosed substance

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
If easy to do, remove contact lens, if worn.  
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : May cause cardiac arrhythmia.
- Other symptoms potentially related to misuse or inhalation abuse are  
Cardiac sensitisation  
Anaesthetic effects  
Light-headedness  
Dizziness  
confusion  
Lack of coordination

# SAFETY DATA SHEET



## Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 14.04.2023
6.1	27.06.2023	1354329-00049	Date of first issue: 27.02.2017

---

Drowsiness  
Unconsciousness

Skin contact may provoke the following symptoms:

Irritation  
Swelling of tissue  
Itching  
Discomfort  
Redness

Eye contact may provoke the following symptoms

tearing  
Redness  
Discomfort

Risks : Causes serious eye irritation.  
May cause drowsiness or dizziness.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, that may be used in situations of emergency life support should be used with special caution.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : None known.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Hydrogen fluoride  
carbonyl fluoride  
Carbon oxides  
Chlorine compounds

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do

# SAFETY DATA SHEET



## Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 14.04.2023
6.1	27.06.2023	1354329-00049	Date of first issue: 27.02.2017

so.  
Evacuate area.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

#### 6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.  
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

#### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.  
Avoid breathing mist or vapours.  
Do not swallow.  
Do not get in eyes.  
Wash skin thoroughly after handling.

# SAFETY DATA SHEET



## Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 14.04.2023
6.1	27.06.2023	1354329-00049	Date of first issue: 27.02.2017

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment

Valve protection caps and valve outlet threaded plugs must remain in place unless container is secured with valve outlet piped to use point.

Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder.

Use a pressure reducing regulator when connecting cylinder to lower pressure (<3000 psig) piping or systems.

Never attempt to lift cylinder by its cap.

Do not drag, slide or roll cylinders.

Use a suitable hand truck for cylinder movement.

Take care to prevent spills, waste and minimize release to the environment.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Cylinders should be stored upright and firmly secured to prevent falling or being knocked over. Separate full containers from empty containers. Do not store near combustible materials. Avoid area where salt or other corrosive materials are present. Do not expose drums to direct heat or temperature above 46°C (115°F) to avoid pressurizing and possibly distorting the drums. Material should not be dispensed by pouring from pail/drum shipping containers containing 5 gallons or more. The use of a drum pump is recommended for dispensing from pail/drum shipping containers with 5 gallons or more, except for smaller containers where adequate ventilation can be used to manage the exposure. Keep in properly labelled containers. Store locked up. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations.

Advice on common storage : No special restrictions on storage with other products.

Storage period : > 10 yr

Recommended storage temperature : < 46 °C

Further information on storage stability : The product has an indefinite shelf life when stored properly.

Keep away from direct sunlight.

### 7.3 Specific end use(s)

Specific use(s) : No data available

# SAFETY DATA SHEET



## Opteon™ XP30 (R-514A) Refrigerant

Version 6.1      Revision Date: 27.06.2023      SDS Number: 1354329-00049      Date of last issue: 14.04.2023  
Date of first issue: 27.02.2017

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

##### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Trans-Dichloroethylene	Workers	Inhalation	Long-term systemic effects	797 mg/m3
	Consumers	Inhalation	Long-term systemic effects	198 mg/m3
	Consumers	Ingestion	Long-term systemic effects	57 mg/kg bw/day

##### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Trans-Dichloroethylene	Fresh water	0,0364 mg/l
	Freshwater - intermittent	0,3636 mg/l
	Marine water	0,0036 mg/l
	Marine sediment	0,055 mg/kg dry weight (d.w.)
	Fresh water sediment	0,5483 mg/kg dry weight (d.w.)
	Sewage treatment plant	17 mg/l
	Soil	0,056 mg/kg dry weight (d.w.)

#### 8.2 Exposure controls

##### Engineering measures

Minimize workplace exposure concentrations.  
If sufficient ventilation is unavailable, use with local exhaust ventilation.

##### Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:  
Safety goggles

Hand protection  
Material : Heat resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

Skin and body protection : Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive

# SAFETY DATA SHEET



## Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 14.04.2023
6.1	27.06.2023	1354329-00049	Date of first issue: 27.02.2017

atmospheres or flash fires, use flame retardant antistatic protective clothing.

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Organic gas and low boiling vapour type (AX)

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: clear
Odour	: slight, ether-like
Odour Threshold	: No data available
pH	: 7
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: 29,1 °C
Flash point	: Method: ASTM D 56 does not flash
Evaporation rate	: No data available
Flammability (solid, gas)	: Not applicable
Upper explosion limit / Upper flammability limit	: Upper flammability limit Method: ASTM E681 None.
Lower explosion limit / Lower flammability limit	: Lower flammability limit Method: ASTM E681 None.
Vapour pressure	: 871,4 hPa (25 °C)
Relative vapour density	: 5,01 (Air = 1.0)
Relative density	: 1,31 (25 °C)
Density	: 1,308 g/cm <sup>3</sup> (25 °C)
Solubility(ies) Water solubility	: No data available



# SAFETY DATA SHEET



## Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 14.04.2023
6.1	27.06.2023	1354329-00049	Date of first issue: 27.02.2017

---

Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

### 9.2 Other information

Flammability (liquids)	:	No data available
Particle size	:	Not applicable

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Not classified as a reactivity hazard.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions	:	None known.
---------------------	---	-------------

### 10.4 Conditions to avoid

Conditions to avoid	:	None known.
---------------------	---	-------------

### 10.5 Incompatible materials

Materials to avoid	:	None.
--------------------	---	-------

### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Information on likely routes of exposure	:	Inhalation Skin contact Ingestion Eye contact
--	---	--

# SAFETY DATA SHEET



## Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 14.04.2023
6.1	27.06.2023	1354329-00049	Date of first issue: 27.02.2017

### Acute toxicity

Not classified based on available information.

### Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

### Components:

#### **(Z)-1,1,1,4,4,4-Hexafluoro-2-butene:**

Acute inhalation toxicity : LC50 (Rat): > 690,413 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403

No observed adverse effect concentration (Dog): 12500 ppm  
Test atmosphere: gas

Lowest observed adverse effect concentration (Dog): 25000 ppm  
Test atmosphere: gas

Cardiac sensitisation threshold limit (Dog): 1.677.740 mg/m3  
Test atmosphere: gas

#### **Trans-Dichloroethylene:**

Acute oral toxicity : LD50 (Rat): 7.902 mg/kg  
Method: OECD Test Guideline 420

Acute inhalation toxicity : Lowest observed adverse effect concentration (Dog): 250000 ppm  
Test atmosphere: gas

Cardiac sensitisation threshold limit (Dog): 991.309 mg/m3  
Test atmosphere: gas

Acute toxicity estimate: 11 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Expert judgement

Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg  
Method: OECD Test Guideline 402

### Skin corrosion/irritation

Not classified based on available information.

### Components:

#### **(Z)-1,1,1,4,4,4-Hexafluoro-2-butene:**

# SAFETY DATA SHEET



## Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 14.04.2023
6.1	27.06.2023	1354329-00049	Date of first issue: 27.02.2017

---

Result : No skin irritation

### Trans-Dichloroethylene:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Mild skin irritation

### Serious eye damage/eye irritation

Causes serious eye irritation.

### Components:

#### (Z)-1,1,1,4,4,4-Hexafluoro-2-butene:

Result : No eye irritation

### Trans-Dichloroethylene:

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : Irritation to eyes, reversing within 7 days

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

### Components:

#### (Z)-1,1,1,4,4,4-Hexafluoro-2-butene:

Exposure routes : Skin contact  
Result : negative

### Germ cell mutagenicity

Not classified based on available information.

### Components:

#### (Z)-1,1,1,4,4,4-Hexafluoro-2-butene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo)

# SAFETY DATA SHEET



## Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 14.04.2023
6.1	27.06.2023	1354329-00049	Date of first issue: 27.02.2017

cytogenetic assay)  
Species: Rat  
Application Route: inhalation (vapour)  
Method: OECD Test Guideline 474  
Result: negative

Germ cell mutagenicity- Assessment : Weight of evidence does not support classification as a germ cell mutagen.

### Trans-Dichloroethylene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Method: OECD Test Guideline 474  
Result: negative

Germ cell mutagenicity- Assessment : Weight of evidence does not support classification as a germ cell mutagen.

### Carcinogenicity

Not classified based on available information.

### Reproductive toxicity

Not classified based on available information.

### Components:


#### (Z)-1,1,1,4,4,4-Hexafluoro-2-butene:

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Method: OECD Test Guideline 416  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Method: OECD Test Guideline 414  
Result: negative

Reproductive toxicity - Assessment : Weight of evidence does not support classification for repro-

# Opteon™ XP30 (R-514A) Refrigerant



### Trans-Dichloroethylene:

## STOT - single exposure

**Components:**

### Trans-Dichloroethylene:

### STOT - repeated exposure

**Components:**

**(Z)-1,1,1,4,4,4-Hexafluoro-2-butene:**

Exposure routes	: inhalation (vapour)
Assessment	: No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or less.

### Trans-Dichloroethylene:

Exposure routes	: Inhalation
Assessment	: No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less.

Exposure routes	: Ingestion
Assessment	: No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

### Repeated dose toxicity

### Components:

**(Z)-1,1,1,4,4,4-Hexafluoro-2-butene:**

Species	: Rat, male and female
NOAEL	: 33,5 mg/l
LOAEL	: 50,3 mg/l
Application Route	: inhalation (vapour)
Exposure time	: 90 d
Method	: OECD Test Guideline 413

### Trans-Dichloroethylene:

Species	:	Rat, male and female
NOAEL	:	4000 ppm
LOAEL	:	> 4000 ppm

# SAFETY DATA SHEET



## Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 14.04.2023
6.1	27.06.2023	1354329-00049	Date of first issue: 27.02.2017

Application Route : Inhalation  
Exposure time : 90 Days  
Method : OECD Test Guideline 413

Species : Rat, male and female  
NOAEL : 3.210 mg/kg  
LOAEL : > 3.210 mg/kg  
Application Route : Ingestion  
Exposure time : 98 Days  
Method : OECD Test Guideline 408

### Aspiration toxicity

Not classified based on available information.

### Components:

#### **(Z)-1,1,1,4,4,4-Hexafluoro-2-butene:**

No aspiration toxicity classification

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

#### **(Z)-1,1,1,4,4,4-Hexafluoro-2-butene:**

Toxicity to fish : LC50 (*Oryzias latipes* (Japanese medaka)): 76,1 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): 22,5 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (*Pseudokirchneriella subcapitata* (green algae)): > 23,7 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

NOEC (*Pseudokirchneriella subcapitata* (green algae)): 6,92 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC: 10 mg/l  
Exposure time: 32 d  
Species: *Gobiocypris rarus* (rare gudgeon)  
Method: OECD Test Guideline 210

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 10 mg/l  
Exposure time: 21 d  
Species: *Daphnia magna* (Water flea)  
Method: OECD Test Guideline 211

# SAFETY DATA SHEET



## Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 14.04.2023
6.1	27.06.2023	1354329-00049	Date of first issue: 27.02.2017

### Trans-Dichloroethylene:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 135 mg/l  
Exposure time: 96 h  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 220 mg/l  
Exposure time: 48 h  
Method: EPA-660/3-75-009

Toxicity to algae/aquatic plants : EbC50 (Pseudokirchneriella subcapitata (green algae)): 36,36 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 201

## 12.2 Persistence and degradability

### Components:

#### (Z)-1,1,1,4,4,4-Hexafluoro-2-butene:

Biodegradability : Result: Not readily biodegradable.  
Method: OECD Test Guideline 302C

### Trans-Dichloroethylene:

Biodegradability : Result: not rapidly degradable  
Method: OECD Test Guideline 301D

## 12.3 Bioaccumulative potential

### Components:

#### (Z)-1,1,1,4,4,4-Hexafluoro-2-butene:

Partition coefficient: n-octanol/water : log Pow: 2,3

### Trans-Dichloroethylene:

Partition coefficient: n-octanol/water : log Pow: 2,06

## 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## 12.6 Other adverse effects

### Product:

# SAFETY DATA SHEET



## Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 14.04.2023
6.1	27.06.2023	1354329-00049	Date of first issue: 27.02.2017

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.  
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.  
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.  
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

### SECTION 14: Transport information

#### 14.1 UN number

ADN : Not regulated as a dangerous good  
ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.2 UN proper shipping name

ADN : Not regulated as a dangerous good  
ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good  
ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.4 Packing group



# SAFETY DATA SHEET



## Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 14.04.2023
6.1	27.06.2023	1354329-00049	Date of first issue: 27.02.2017

ADN	:	Not regulated as a dangerous good
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA (Cargo)	:	Not regulated as a dangerous good
IATA (Passenger)	:	Not regulated as a dangerous good

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Not applicable

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2 Chemical safety assessment

Chemical Safety Assessments have been carried out for these substances.

## SECTION 16: Other information

Other information : Opteon™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.  
Chemours™ and the Chemours Logo are trademarks of The Chemours Company.  
Before use read Chemours safety information.  
For further information contact the local Chemours office or nominated distributors.

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

### Full text of H-Statements

H225	:	Highly flammable liquid and vapour.
H319	:	Causes serious eye irritation.
H332	:	Harmful if inhaled.
H336	:	May cause drowsiness or dizziness.
H412	:	Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
STOT SE	:	Specific target organ toxicity - single exposure

## Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 14.04.2023
6.1	27.06.2023	1354329-00049	Date of first issue: 27.02.2017

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

**Further information**

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

**Classification of the mixture:**

Eye Irrit. 2	H319
STOT SE 3	H336
Aquatic Chronic 3	H412

**Classification procedure:**

Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

# SAFETY DATA SHEET



## Opteon™ XP30 (R-514A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 14.04.2023
6.1	27.06.2023	1354329-00049	Date of first issue: 27.02.2017

---

EG / EN