

# SAFETY DATA SHEET



## Freon™ 134a (HFC-134a) Refrigerant - Propellant

Version	Revision Date:	SDS Number:	Date of last issue: 2022/12/05
7.8	2023/04/14	1325510-00047	Date of first issue: 2017/02/27

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Freon™ 134a (HFC-134a) Refrigerant - Propellant

SDS-Identcode : 130000000349

Other means of identification : None

#### Recommended use of the chemical and restrictions on use

Recommended use : Refrigerant

Restrictions on use : For professional and industrial installation and use only.

#### Manufacturer or supplier's details

Company : The Chemours (Taiwan) Company Limited

Address : 14th Floor, Hung Kuo Building, 167 Tun Hwa North Road, Taipei, Taiwan

Telephone : 0080-112-7758

Emergency telephone number : 0800 055 119 (in case of chemical spill, fire or poisoning accident)

Telefax : 02-2719-8516

### 2. HAZARDS IDENTIFICATION

#### GHS Classification

Gases under pressure : Liquefied gas

#### GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H280 Contains gas under pressure; may explode if heated.

Precautionary statements : **Storage:**  
P410 + P403 Protect from sunlight. Store in a well-ventilated place.

# SAFETY DATA SHEET



## Freon™ 134a (HFC-134a) Refrigerant - Propellant

Version	Revision Date:	SDS Number:	Date of last issue: 2022/12/05
7.8	2023/04/14	1325510-00047	Date of first issue: 2017/02/27

### Other hazards which do not result in classification

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.

Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.

Rapid evaporation of the product may cause frostbite.

May displace oxygen and cause rapid suffocation.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	:	Substance
Substance name	:	1,1,1,2-Tetrafluoroethane
CAS-No.	:	811-97-2
Synonyms	:	HFC-134a

#### Components

Hazardous ingredients	CAS-No.	Concentration (% w/w)
1,1,1,2-Tetrafluoroethane#	811-97-2	>= 99.9 -<= 100

# Voluntarily-disclosed substance

### 4. FIRST AID MEASURES

General advice	:	In the case of accident or if you feel unwell, seek medical advice immediately. When symptoms persist or in all cases of doubt seek medical advice.
----------------	---	--

#### First aid measures for different exposure routes

If inhaled	:	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
In case of skin contact	:	Thaw frosted parts with lukewarm water. Do not rub affected area. Get medical attention immediately.
In case of eye contact	:	Get medical attention immediately.
If swallowed	:	Ingestion is not considered a potential route of exposure.
Most important symptoms and effects, both acute and delayed	:	May cause cardiac arrhythmia. Other symptoms potentially related to misuse or inhalation abuse are Cardiac sensitisation Anaesthetic effects Light-headedness Dizziness

# SAFETY DATA SHEET



## Freon™ 134a (HFC-134a) Refrigerant - Propellant

Version 7.8	Revision Date: 2023/04/14	SDS Number: 1325510-00047	Date of last issue: 2022/12/05 Date of first issue: 2017/02/27
----------------	------------------------------	------------------------------	---

confusion  
Lack of coordination  
Drowsiness  
Unconsciousness  
Gas reduces oxygen available for breathing.  
Contact with liquid or refrigerated gas can cause cold burns and frostbite.

Protection of first-aiders : No special precautions are necessary for first aid responders.

Notes to physician : Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, that may be used in situations of emergency life support should be used with special caution.

### 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Not applicable  
Will not burn

Unsuitable extinguishing media : Not applicable  
Will not burn

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Hydrogen fluoride  
carbonyl fluoride  
Carbon oxides

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Fight fire remotely due to the risk of explosion.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.  
Use personal protective equipment.

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.  
Avoid skin contact with leaking liquid (danger of frostbite).  
Ventilate the area.  
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.  
Prevent further leakage or spillage if safe to do so.

# SAFETY DATA SHEET



## Freon™ 134a (HFC-134a) Refrigerant - Propellant

Version 7.8	Revision Date: 2023/04/14	SDS Number: 1325510-00047	Date of last issue: 2022/12/05 Date of first issue: 2017/02/27
----------------	------------------------------	------------------------------	---

Retain and dispose of contaminated wash water.

Methods and materials for containment and cleaning up : Ventilate the area.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### 7. HANDLING AND STORAGE

#### Handling

Technical measures : Use equipment rated for cylinder pressure. Use a backflow preventative device in piping. Close valve after each use and when empty.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Avoid breathing gas.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Wear cold insulating gloves/ face shield/ eye protection.  
Valve protection caps and valve outlet threaded plugs must remain in place unless container is secured with valve outlet piped to use point.  
Prevent backflow into the gas tank.  
Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder.  
Use a pressure reducing regulator when connecting cylinder to lower pressure (<3000 psig) piping or systems.  
Close valve after each use and when empty. Do NOT change or force fit connections.  
Prevent the intrusion of water into the gas tank.  
Never attempt to lift cylinder by its cap.  
Do not drag, slide or roll cylinders.  
Use a suitable hand truck for cylinder movement.  
Keep away from heat and sources of ignition.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.

#### Storage

Conditions for safe storage : Cylinders should be stored upright and firmly secured to prevent falling or being knocked over.  
Separate full containers from empty containers.  
Do not store near combustible materials.  
Avoid area where salt or other corrosive materials are present.  
Keep in properly labelled containers.  
Keep in a cool, well-ventilated place.

# SAFETY DATA SHEET



## Freon™ 134a (HFC-134a) Refrigerant - Propellant

Version 7.8	Revision Date: 2023/04/14	SDS Number: 1325510-00047	Date of last issue: 2022/12/05 Date of first issue: 2017/02/27
----------------	------------------------------	------------------------------	---

Keep away from direct sunlight.  
Store in accordance with the particular national regulations.

Materials to avoid	:	Do not store with the following product types: Strong oxidizing agents
Recommended storage temperature	:	< 52 °C
Storage period	:	> 10 yr
Further information on storage stability	:	The product has an indefinite shelf life when stored properly.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Contains no substances with occupational exposure limit values.

#### Biological occupational exposure limits

Contains no substances with biological exposure indices.

Engineering measures	:	Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations.
----------------------	---	---

#### Personal protective equipment

Respiratory protection	:	If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
------------------------	---	--

Filter type	:	Organic gas and low boiling vapour type
-------------	---	---

Hand protection Material	:	Low temperature resistant gloves
-----------------------------	---	----------------------------------

Remarks	:	Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!
---------	---	---

Eye protection	:	Wear the following personal protective equipment: Chemical resistant goggles must be worn. Face-shield
----------------	---	--

Skin and body protection	:	Skin should be washed after contact.
--------------------------	---	--------------------------------------

# SAFETY DATA SHEET



## Freon™ 134a (HFC-134a) Refrigerant - Propellant

Version 7.8	Revision Date: 2023/04/14	SDS Number: 1325510-00047	Date of last issue: 2022/12/05 Date of first issue: 2017/02/27
----------------	------------------------------	------------------------------	---

Protective measures : Wear cold insulating gloves/ face shield/ eye protection.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Liquefied gas

Colour : colourless

Odour : slight, ether-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : -108 °C

Initial boiling point and boiling range : -26 °C  
(1,013 hPa)

Flash point : Not applicable

Evaporation rate : > 1  
(CCL4=1.0)

Flammability (solid, gas) : Will not burn

Self-ignition : The substance or mixture is not classified as pyrophoric.

Upper explosion limit / Upper flammability limit : Upper flammability limit  
Method: ASTM E681  
None.

Lower explosion limit / Lower flammability limit : Lower flammability limit  
Method: ASTM E681  
None.

Vapour pressure : 5,700 hPa (20 °C)

Relative vapour density : No data available

Relative density : 1.208 (25 °C)

# SAFETY DATA SHEET



## Freon™ 134a (HFC-134a) Refrigerant - Propellant

Version 7.8	Revision Date: 2023/04/14	SDS Number: 1325510-00047	Date of last issue: 2022/12/05 Date of first issue: 2017/02/27
----------------	------------------------------	------------------------------	---

Density	:	1.21 g/cm <sup>3</sup> (25 °C) (as liquid)
Solubility(ies) Water solubility	:	1.5 g/l (25 °C)
Partition coefficient: n-octanol/water	:	log Pow: 1.06 (25 °C)
Auto-ignition temperature	:	> 743 °C
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	Not applicable

### 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable if used as directed. Follow precautionary advice and avoid incompatible materials and conditions.
Possibility of hazardous reactions	:	Can react with strong oxidizing agents.
Conditions to avoid	:	This substance is not flammable in air at temperatures up to 100 °C (212 °F) at atmospheric pressure. However, mixtures of this substance with high concentrations of air at elevated pressure and/or temperature can become combustible in the presence of an ignition source. This substance can also become combustible in an oxygen enriched environment (oxygen concentrations greater than that in air). Whether a mixture containing this substance and air, or this substance in an oxygen enriched atmosphere become combustible depends on the inter-relationship of 1) the temperature 2) the pressure, and 3) the proportion of oxygen in the mixture. In general, this substance should not be allowed to exist with air above atmospheric pressure or at high temperatures; or in an oxygen enriched environment. For example this substance should NOT be mixed with air under pressure for leak testing or other purposes. Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents

# SAFETY DATA SHEET



## Freon™ 134a (HFC-134a) Refrigerant - Propellant

Version 7.8	Revision Date: 2023/04/14	SDS Number: 1325510-00047	Date of last issue: 2022/12/05 Date of first issue: 2017/02/27
----------------	------------------------------	------------------------------	---

Hazardous decomposition products : No hazardous decomposition products are known.

### 11. TOXICOLOGICAL INFORMATION

Exposure routes : Inhalation  
Skin contact  
Eye contact

Symptoms of Overexposure : May cause cardiac arrhythmia.  
Other symptoms potentially related to misuse or inhalation abuse are  
Cardiac sensitisation  
Anaesthetic effects  
Light-headedness  
Dizziness  
confusion  
Lack of coordination  
Drowsiness  
Unconsciousness

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **1,1,1,2-Tetrafluoroethane:**

Acute oral toxicity : Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 567000 ppm  
Exposure time: 4 h  
Test atmosphere: gas  
Method: OECD Test Guideline 403

No observed adverse effect concentration (Dog): 40000 ppm  
Test atmosphere: gas  
Remarks: Cardiac sensitisation

Lowest observed adverse effect concentration (Dog): 80000 ppm  
Test atmosphere: gas  
Symptoms: May cause cardiac arrhythmia.

Cardiac sensitisation threshold limit (Dog): 334,000 mg/m3  
Test atmosphere: gas  
Symptoms: May cause cardiac arrhythmia.

Acute dermal toxicity : Assessment: The substance or mixture has no acute dermal toxicity



# SAFETY DATA SHEET



## Freon™ 134a (HFC-134a) Refrigerant - Propellant

Version	Revision Date:	SDS Number:	Date of last issue: 2022/12/05
7.8	2023/04/14	1325510-00047	Date of first issue: 2017/02/27

---

### Skin corrosion/irritation

Not classified based on available information.

#### Components:

##### 1,1,1,2-Tetrafluoroethane:

Result : No skin irritation

### Serious eye damage/eye irritation

Not classified based on available information.

#### Components:

##### 1,1,1,2-Tetrafluoroethane:

Result : No eye irritation

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

#### Components:

##### 1,1,1,2-Tetrafluoroethane:

Exposure routes : Skin contact  
Result : negative

Exposure routes : Inhalation  
Species : Rat  
Result : negative

Exposure routes : Inhalation  
Species : Humans  
Result : negative

### Chronic toxicity

#### Germ cell mutagenicity

Not classified based on available information.

#### Components:

##### 1,1,1,2-Tetrafluoroethane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

# SAFETY DATA SHEET



## Freon™ 134a (HFC-134a) Refrigerant - Propellant

Version 7.8	Revision Date: 2023/04/14	SDS Number: 1325510-00047	Date of last issue: 2022/12/05 Date of first issue: 2017/02/27
----------------	------------------------------	------------------------------	---

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative

Test Type: Unscheduled DNA synthesis (UDS) test with mammalian liver cells in vivo  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 486  
Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

### Carcinogenicity

Not classified based on available information.

#### Components:

##### **1,1,1,2-Tetrafluoroethane:**

Species : Rat  
Application Route : inhalation (gas)  
Exposure time : 2 Years  
Method : OECD Test Guideline 453  
Result : negative

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

### Reproductive toxicity

Not classified based on available information.

#### Components:

##### **1,1,1,2-Tetrafluoroethane:**

Effects on fertility : Species: Mouse  
Application Route: Inhalation  
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rabbit  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 414  
Result: negative

Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity

# SAFETY DATA SHEET



## Freon™ 134a (HFC-134a) Refrigerant - Propellant

Version	Revision Date:	SDS Number:	Date of last issue: 2022/12/05
7.8	2023/04/14	1325510-00047	Date of first issue: 2017/02/27

### STOT - single exposure

Not classified based on available information.

#### Components:

##### 1,1,1,2-Tetrafluoroethane:

Exposure routes	: inhalation (gas)
Assessment	: No significant health effects observed in animals at concentrations of 20000 ppmV/4h or less

### STOT - repeated exposure

Not classified based on available information.

#### Components:

##### 1,1,1,2-Tetrafluoroethane:

Exposure routes	: inhalation (gas)
Assessment	: No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less.

### Repeated dose toxicity

#### Components:

##### 1,1,1,2-Tetrafluoroethane:

Species	: Rat, male and female
NOAEL	: 50000 ppm
LOAEL	: >50000 ppm
Application Route	: inhalation (gas)
Exposure time	: 2 yr
Method	: OECD Test Guideline 453

### Aspiration toxicity

Not classified based on available information.

#### Components:

##### 1,1,1,2-Tetrafluoroethane:

No aspiration toxicity classification

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

##### 1,1,1,2-Tetrafluoroethane:

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): 450 mg/l Exposure time: 96 h Method: Regulation (EC) No. 440/2008, Annex, C.1
Toxicity to daphnia and other	: EC50 (Daphnia magna (Water flea)): 980 mg/l

# SAFETY DATA SHEET



## Freon™ 134a (HFC-134a) Refrigerant - Propellant

Version 7.8	Revision Date: 2023/04/14	SDS Number: 1325510-00047	Date of last issue: 2022/12/05 Date of first issue: 2017/02/27
----------------	------------------------------	------------------------------	---

aquatic invertebrates      Exposure time: 48 h  
Method: Regulation (EC) No. 440/2008, Annex, C.2

Toxicity to algae/aquatic plants      : ErC50 (green algae): > 100 mg/l  
Exposure time: 96 h  
Remarks: Based on data from similar materials

### Persistence and degradability

#### Components:

##### **1,1,1,2-Tetrafluoroethane:**

Biodegradability      : Result: Not readily biodegradable.  
Method: OECD Test Guideline 301D

### Bioaccumulative potential

#### Components:

##### **1,1,1,2-Tetrafluoroethane:**

Bioaccumulation      : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water      : log Pow: 1.06

### Mobility in soil

No data available

### Other adverse effects

No data available

---

## 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues      : Dispose of in accordance with local regulations.

Contaminated packaging      : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty pressure vessels should be returned to the supplier.  
If not otherwise specified: Dispose of as unused product.

---

## 14. TRANSPORT INFORMATION

### International Regulations

#### **UNRTDG**

UN number	: UN 3159
Proper shipping name	: 1,1,1,2-TETRAFLUOROETHANE
Class	: 2.2
Packing group	: Not assigned by regulation
Labels	: 2.2

# SAFETY DATA SHEET



## Freon™ 134a (HFC-134a) Refrigerant - Propellant

Version	Revision Date:	SDS Number:	Date of last issue: 2022/12/05
7.8	2023/04/14	1325510-00047	Date of first issue: 2017/02/27

### IATA-DGR

UN/ID No.	: UN 3159
Proper shipping name	: 1,1,1,2-Tetrafluoroethane
Class	: 2.2
Packing group	: Not assigned by regulation
Labels	: Non-flammable, non-toxic Gas
Packing instruction (cargo aircraft)	: 200
Packing instruction (passenger aircraft)	: 200

### IMDG-Code

UN number	: UN 3159
Proper shipping name	: 1,1,1,2-TETRAFLUOROETHANE
Class	: 2.2
Packing group	: Not assigned by regulation
Labels	: 2.2
EmS Code	: F-C, S-V
Marine pollutant	: no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 15. REGULATORY INFORMATION

### National regulatory information

Regulations on Occupational Safety and Health Facilities  
Standards for the Storage, Cleanup, Handling and Disposal of Industrial Waste  
Regulations on Labelling and Hazard Communication of Hazardous Chemicals  
Rules on Road Traffic Safety

Montreal Protocol	: 1,1,1,2-Tetrafluoroethane
-------------------	-----------------------------

## 16. OTHER INFORMATION

Other information	: Freon™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC. Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information. For further information contact the local Chemours office or nominated distributors.
-------------------	--

### Further information

Sources of key data used to	: Internal technical data, data from raw material SDSs, OECD
-----------------------------	--

# SAFETY DATA SHEET



## Freon™ 134a (HFC-134a) Refrigerant - Propellant

Version 7.8	Revision Date: 2023/04/14	SDS Number: 1325510-00047	Date of last issue: 2022/12/05 Date of first issue: 2017/02/27
----------------	------------------------------	------------------------------	---

compile the Safety Data Sheet      eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Responsible Department : 130000000349  
The Chemours (Taiwan) Company Limited  
Product Sustainability Department  
14th Floor, Hung Kuo Building, 167 Tun Hwa North Road,  
Taipei, Taiwan

Prepared by : 0080-112-7758  
Zhenwen Tu / Product Stewardship and Regulatory Compliance Expert

Revision Date : 2023/04/14

Date format : yyyy/mm/dd

### Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

# SAFETY DATA SHEET



## Freon™ 134a (HFC-134a) Refrigerant - Propellant

Version	Revision Date:	SDS Number:	Date of last issue: 2022/12/05
7.8	2023/04/14	1325510-00047	Date of first issue: 2017/02/27

---

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

TW / EN