

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Viton™ VTR-9093 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 10.09.2020
3.8	02.04.2021	1330595-00039	Date of first issue: 27.02.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Viton™ VTR-9093 fluoroelastomer

SDS-Identcode : 130000026659

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Rubber products, Resin for moulding and/or extrusion

Recommended restrictions
on use : For professional users only.
Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

1.3 Details of the supplier of the safety data sheet

Company : Chemours Netherlands B.V.
Baanhoekweg 22
3313 LA Dordrecht Netherlands

Telephone : +31-(0)-78-630-1011

Telefax : +31-78-6163737

E-mail address of person
responsible for the SDS : sds-support@chemours.com

1.4 Emergency telephone number

+(44)-870-8200418 (CHEMTREC - Recommended)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Additional Labelling

EUH210 Safety data sheet available on request.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Viton™ VTR-9093 fluoroelastomer

Version 3.8 Revision Date: 02.04.2021 SDS Number: 1330595-00039 Date of last issue: 10.09.2020
Date of first issue: 27.02.2017

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
4,4'- (Hexafluoroisopropylidene)diphenol	1478-61-1 216-036-7 01-2120762844-45-0004	Eye Dam. 1; H318 Repr. 1B; H360 STOT RE 2; H373 (Prostate, Seminal vesicle) Aquatic Chronic 1; H410 M-Factor (Chronic aquatic toxicity): 1	>= 1 - < 2.5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Protection of first-aiders : No special precautions are necessary for first aid responders.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : Wash with water and soap as a precaution.
Get medical attention if symptoms occur.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Viton™ VTR-9093 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 10.09.2020
3.8	02.04.2021	1330595-00039	Date of first issue: 27.02.2017

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Fluorine compounds
Hydrogen fluoride
carbonyl fluoride
potentially toxic fluorinated compounds
aerosolized particulates

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Sweep up or vacuum up spillage and collect in suitable con-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Viton™ VTR-9093 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 10.09.2020
3.8	02.04.2021	1330595-00039	Date of first issue: 27.02.2017

tainer for disposal.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- | | | |
|-------------------------|---|--|
| Technical measures | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : | Use only with adequate ventilation. |
| Advice on safe handling | : | Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment. |
| Hygiene measures | : | If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use. |

7.2 Conditions for safe storage, including any incompatibilities

- | | | |
|---|---|---|
| Requirements for storage areas and containers | : | Keep in properly labelled containers. Store in accordance with the particular national regulations. |
| Advice on common storage | : | No special restrictions on storage with other products. |

7.3 Specific end use(s)

- | | | |
|-----------------|---|-------------------|
| Specific use(s) | : | No data available |
|-----------------|---|-------------------|

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Hydrofluoric acid	7664-39-3	TWA	1.8 ppm	2000/39/EC

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Viton™ VTR-9093 fluoroelastomer

Version
3.8

Revision Date:
02.04.2021

SDS Number:
1330595-00039

Date of last issue: 10.09.2020
Date of first issue: 27.02.2017

			1.5 mg/m3	
	Further information: Indicative			
		STEL	3 ppm 2.5 mg/m3	2000/39/EC
	Further information: Indicative			
		TWA	1.8 ppm 1.5 mg/m3 (Fluorine)	GB EH40
		STEL	3 ppm 2.5 mg/m3 (Fluorine)	GB EH40
Carbonyl difluoride	353-50-4	TWA	2.5 mg/m3 (Fluorine)	2000/39/EC
	Further information: Indicative			
Carbon dioxide	124-38-9	TWA	5,000 ppm 9,000 mg/m3	2006/15/EC
	Further information: Indicative			
		TWA	5,000 ppm 9,150 mg/m3	GB EH40
		STEL	15,000 ppm 27,400 mg/m3	GB EH40
Carbon monoxide	630-08-0	TWA	20 ppm 23 mg/m3	GB EH40
		STEL	100 ppm 117 mg/m3	GB EH40
		TWA	20 ppm 23 mg/m3	2017/164/EU
	Further information: Indicative			
		STEL	100 ppm 117 mg/m3	2017/164/EU
	Further information: Indicative			
		TWA	30 ppm 35 mg/m3	GB EH40
	Further information: Limits applicable to underground mining & tunnelling industries ONLY until 21/8/23			
		STEL	200 ppm 232 mg/m3	GB EH40
	Further information: Limits applicable to underground mining & tunnelling industries ONLY until 21/8/23			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
4,4'-(Hexafluoroisopropylidene)diphenol	Workers	Inhalation	Long-term systemic effects	0.118 mg/m3
	Workers	Skin contact	Long-term systemic effects	0.033 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0.029 mg/m3
	Consumers	Dermal	Long-term systemic effects	0.017 mg/kg bw/day
	Consumers	Oral	Long-term systemic	0.017 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Viton™ VTR-9093 fluoroelastomer

Version 3.8 Revision Date: 02.04.2021 SDS Number: 1330595-00039 Date of last issue: 10.09.2020
Date of first issue: 27.02.2017

			effects	bw/day
--	--	--	---------	--------

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
4,4'-(Hexafluoroisopropylidene)diphenol	Freshwater - intermittent	0.027 mg/l
	Fresh water	0.00522 mg/l
	Fresh water sediment	1.21 mg/kg dry weight (d.w.)
	Marine water - intermittent	0.027 mg/l
	Marine water	0.000522 mg/l
	Marine sediment	0.121 mg/kg dry weight (d.w.)
	Sewage treatment plant	4.787 mg/l
	Soil	0.239 mg/kg dry weight (d.w.)

8.2 Exposure controls

Engineering measures

Processing may form hazardous compounds (see section 10).
Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Eye protection : Wear the following personal protective equipment:
Safety glasses
Equipment should conform to BS EN 166

Hand protection
Material : Nitrile rubber
Glove thickness : 0.38 mm
Wearing time : 480 min

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

Skin and body protection : Skin should be washed after contact.

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
Equipment should conform to BS EN 14387

Filter type : Combined particulates and acidic gas/vapour type (E-P)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Viton™ VTR-9093 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 10.09.2020
3.8	02.04.2021	1330595-00039	Date of first issue: 27.02.2017

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: sheets
Colour	: white, off-white
Odour	: odourless
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: No data available
Flash point	: Not applicable
Evaporation rate	: Not applicable
Flammability (solid, gas)	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: Not applicable
Relative vapour density	: Not applicable
Density	: 1.75 - 1.90 g/cm ³
Solubility(ies)	
Water solubility	: insoluble
Partition coefficient: n-octanol/water	: Not applicable
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, kinematic	: Not applicable
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Viton™ VTR-9093 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 10.09.2020
3.8	02.04.2021	1330595-00039	Date of first issue: 27.02.2017

9.2 Other information

Particle size : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Hazardous decomposition products will be formed at elevated temperatures.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : None.

10.6 Hazardous decomposition products

Thermal decomposition : Hydrofluoric acid
Carbonyl difluoride
Carbon dioxide
Carbon monoxide

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Assessment: The substance or mixture has no acute oral toxicity

Components:

4,4'-(Hexafluoroisopropylidene)diphenol:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 423
Assessment: The substance or mixture has no acute oral toxicity

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Viton™ VTR-9093 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 10.09.2020
3.8	02.04.2021	1330595-00039	Date of first issue: 27.02.2017

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:

4,4'-(Hexafluoroisopropylidene)diphenol:

Species	: Rabbit
Method	: OECD Test Guideline 404
Result	: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result : No eye irritation

Components:

4,4'-(Hexafluoroisopropylidene)diphenol:

Species	: Rabbit
Method	: OECD Test Guideline 405
Result	: Irreversible effects on the eye

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

4,4'-(Hexafluoroisopropylidene)diphenol:

Test Type	: Maximisation Test
Exposure routes	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative

Germ cell mutagenicity

Not classified based on available information.

Components:

4,4'-(Hexafluoroisopropylidene)diphenol:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Viton™ VTR-9093 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 10.09.2020
3.8	02.04.2021	1330595-00039	Date of first issue: 27.02.2017

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Method: OPPTS 870.5300
Result: equivocal

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

Product:

Reproductive toxicity - Assessment : No toxicity to reproduction

Components:

4,4'-(Hexafluoroisopropylidene)diphenol:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: positive

Effects on foetal development : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Reproductive toxicity - Assessment : Clear evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Product:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Components:

4,4'-(Hexafluoroisopropylidene)diphenol:

Exposure routes : Ingestion

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Viton™ VTR-9093 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 10.09.2020
3.8	02.04.2021	1330595-00039	Date of first issue: 27.02.2017

Target Organs : Prostate, Seminal vesicle
Assessment : Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.

Repeated dose toxicity

Components:

4,4'-(Hexafluoroisopropylidene)diphenol:

Species : Rat, male and female
NOAEL : 10 mg/kg
LOAEL : 30 mg/kg
Application Route : Ingestion
Exposure time : 28 Days
Method : OECD Test Guideline 407

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : According to data on similar materials, and from modeling assessment, the product is not considered to require classification as dangerous to health.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Components:

4,4'-(Hexafluoroisopropylidene)diphenol:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 4.2 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 215

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 2.7 mg/l
aquatic invertebrates
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : ErC50 (Desmodesmus subspicatus (green algae)): 3 mg/l
plants
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.052 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Viton™ VTR-9093 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 10.09.2020
3.8	02.04.2021	1330595-00039	Date of first issue: 27.02.2017

Exposure time: 3 d
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC: 0.125 mg/l
Exposure time: 120 d
Species: Danio rerio (zebra fish)
Method: No data available

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.23 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

M-Factor (Chronic aquatic toxicity) : 1

12.2 Persistence and degradability

Components:

4,4'-(Hexafluoroisopropylidene)diphenol:

Biodegradability : Result: Not readily biodegradable.
Method: OECD Test Guideline 301B

12.3 Bioaccumulative potential

Components:

4,4'-(Hexafluoroisopropylidene)diphenol:

Bioaccumulation : Species: Zebrafish
Bioconcentration factor (BCF): 9.8
Method: OECD Test Guideline 305

Partition coefficient: n-octanol/water : log Pow: 2.79

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Viton™ VTR-9093 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 10.09.2020
3.8	02.04.2021	1330595-00039	Date of first issue: 27.02.2017

(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : According to data on similar materials, and from modelling assessment, the product is not considered to require classification as dangerous to the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal. If not otherwise specified: Dispose of as unused product.

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Cadmium (Number on list 72, 28) Nickel (Number on list 27)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Viton™ VTR-9093 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 10.09.2020
3.8	02.04.2021	1330595-00039	Date of first issue: 27.02.2017

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Viton™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.
Chemours™ and the Chemours Logo are trademarks of The Chemours Company.
Before use read Chemours safety information.
For further information contact the local Chemours office or nominated distributors.

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H318 : Causes serious eye damage.
H360 : May damage fertility or the unborn child.
H373 : May cause damage to organs through prolonged or repeated exposure.
H410 : Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard
Eye Dam. : Serious eye damage
Repr. : Reproductive toxicity
STOT RE : Specific target organ toxicity - repeated exposure
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2006/15/EC : Europe. Indicative occupational exposure limit values

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Viton™ VTR-9093 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 10.09.2020
3.8	02.04.2021	1330595-00039	Date of first issue: 27.02.2017

2017/164/EU	:	Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
2006/15/EC / TWA	:	Limit Value - eight hours
2017/164/EU / STEL	:	Short term exposure limit
2017/164/EU / TWA	:	Limit Value - eight hours
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Viton™ VTR-9093 fluoroelastomer

Version	Revision Date:	SDS Number:	Date of last issue: 10.09.2020
3.8	02.04.2021	1330595-00039	Date of first issue: 27.02.2017

Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN