

# SAFETY DATA SHEET



## Ti-Pure™ R-796+ Titanium Dioxide Pigment

Version 4.7      Revision Date: 10/18/2022      SDS Number: 1560916-00012      Date of last issue: 09/15/2021  
Date of first issue: 04/21/2017

### SECTION 1. IDENTIFICATION

Product name : Ti-Pure™ R-796+ Titanium Dioxide Pigment

SDS-Identcode : 130000043365

#### Manufacturer or supplier's details

Company name of supplier : The Chemours Company FC, LLC

Address : 1007 Market Street  
Wilmington, DE 19801 United States of America (USA)

Telephone : 1-844-773-CHEM (outside the U.S. 1-302-773-1000)

Emergency telephone : Medical emergency: 1-866-595-1473 (outside the U.S. 1-302-773-2000) ; Transport emergency: +1-800-424-9300 (outside the U.S. +1-703-527-3887)

#### Recommended use of the chemical and restrictions on use

Recommended use : Coloring agent  
Pigment

Restrictions on use : For industrial use only.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

#### GHS label elements

Not a hazardous substance or mixture.

#### Other hazards

None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
Titanium dioxide	13463-67-7	$\geq 90 - \leq 100$
Laminate component	Trade secret	$\geq 5 - < 10$
Aluminium hydroxide	21645-51-2	$\geq 1 - < 5$

Actual concentration is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

# SAFETY DATA SHEET



## Ti-Pure™ R-796+ Titanium Dioxide Pigment

Version 4.7	Revision Date: 10/18/2022	SDS Number: 1560916-00012	Date of last issue: 09/15/2021 Date of first issue: 04/21/2017
----------------	------------------------------	------------------------------	---

If inhaled	: If inhaled, remove to fresh air. Get medical attention if symptoms occur.
In case of skin contact	: Wash with water and soap as a precaution. Get medical attention if symptoms occur.
In case of eye contact	: Flush eyes with water as a precaution. Get medical attention if irritation develops and persists.
If swallowed	: If swallowed, DO NOT induce vomiting. Get medical attention if symptoms occur. Rinse mouth thoroughly with water.
Most important symptoms and effects, both acute and delayed	: irritant effects
Protection of first-aiders	: No special precautions are necessary for first aid responders.
Notes to physician	: Treat symptomatically and supportively.

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Not applicable Will not burn
Unsuitable extinguishing media	: Not applicable Will not burn
Specific hazards during fire fighting	: Exposure to combustion products may be a hazard to health.
Hazardous combustion products	: Carbon oxides Metal oxides
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for fire-fighters	: Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
Environmental precautions	: Avoid release to the environment.

# SAFETY DATA SHEET



## Ti-Pure™ R-796+ Titanium Dioxide Pigment

Version 4.7      Revision Date: 10/18/2022      SDS Number: 1560916-00012      Date of last issue: 09/15/2021  
Date of first issue: 04/21/2017

Prevent further leakage or spillage if safe to do so.  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.  
Store in accordance with the particular national regulations.

Materials to avoid : No special restrictions on storage with other products.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Respirable particulate matter)	2.5 mg/m <sup>3</sup> (Titanium dioxide)	ACGIH
		TWA (Respirable particulate matter)	0.2 mg/m <sup>3</sup> (Titanium dioxide)	ACGIH
Laminate component	Trade secret	TWA (Respirable particulate matter)	1 mg/m <sup>3</sup> (Aluminum)	ACGIH

# SAFETY DATA SHEET



## Ti-Pure™ R-796+ Titanium Dioxide Pigment

Version 4.7      Revision Date: 10/18/2022      SDS Number: 1560916-00012      Date of last issue: 09/15/2021  
Date of first issue: 04/21/2017

Aluminium hydroxide	21645-51-2	TWA (Respirable particulate matter)	1 mg/m <sup>3</sup> (Aluminum)	ACGIH
---------------------	------------	-------------------------------------	--------------------------------	-------

**Engineering measures** : Ensure adequate ventilation, especially in confined areas.  
Minimize workplace exposure concentrations.

### Personal protective equipment

**Respiratory protection** : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

**Hand protection**

**Remarks** : Wash hands before breaks and at the end of workday.

**Eye protection** : Wear the following personal protective equipment:  
Safety glasses

**Skin and body protection** : Skin should be washed after contact.

**Hygiene measures** : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** : crystalline

**Color** : white

**Odor** : odorless

**Odor Threshold** : No data available

**pH** : No data available

**Melting point/freezing point** : 3,349 °F / 1,843 °C

# SAFETY DATA SHEET



## Ti-Pure™ R-796+ Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 09/15/2021
4.7	10/18/2022	1560916-00012	Date of first issue: 04/21/2017

---

Initial boiling point and boiling range	:	5,432 °F / 3,000 °C
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Will not burn
		Not expected to form explosive dust-air mixtures.
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	Not applicable
Relative vapor density	:	Not applicable
Relative density	:	3.6 - 4.3
Solubility(ies)		
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	The substance or mixture is not classified self-reactive.
Viscosity		
Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	No data available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	None known.

# SAFETY DATA SHEET



## Ti-Pure™ R-796+ Titanium Dioxide Pigment

Version 4.7	Revision Date: 10/18/2022	SDS Number: 1560916-00012	Date of last issue: 09/15/2021 Date of first issue: 04/21/2017
----------------	------------------------------	------------------------------	---

Conditions to avoid	: None known.
Incompatible materials	: None.
Hazardous decomposition products	: No hazardous decomposition products are known.

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **Titanium dioxide:**

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 425
Acute inhalation toxicity	: LC50 (Rat): > 6.82 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	: Acute toxicity estimate (Rat): > 2,000 mg/kg Method: Expert judgment Assessment: The substance or mixture has no acute dermal toxicity

##### **Laminate component:**

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 5.1 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: OECD Test Guideline 403 Assessment: The substance or mixture has no acute inhalation toxicity Remarks: Based on data from similar materials
Acute dermal toxicity	: LD50 (Rabbit): > 4,640 mg/kg Assessment: The substance or mixture has no acute dermal toxicity

##### **Aluminium hydroxide:**

Acute oral toxicity	: LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 423 Assessment: The substance or mixture has no acute oral toxicity
---------------------	---

# SAFETY DATA SHEET



## Ti-Pure™ R-796+ Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 09/15/2021
4.7	10/18/2022	1560916-00012	Date of first issue: 04/21/2017

---

Acute inhalation toxicity : LC50 (Rat): > 5.09 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: Based on data from similar materials

### Skin corrosion/irritation

Not classified based on available information.

#### Components:

##### **Titanium dioxide:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

##### **Laminate component:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
Remarks : Information given is based on data obtained from similar substances.

##### **Aluminium hydroxide:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

### Serious eye damage/eye irritation

Not classified based on available information.

#### Components:

##### **Titanium dioxide:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

##### **Laminate component:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405  
Remarks : Based on data from similar materials

##### **Aluminium hydroxide:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

# SAFETY DATA SHEET



## Ti-Pure™ R-796+ Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 09/15/2021
4.7	10/18/2022	1560916-00012	Date of first issue: 04/21/2017

---

### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

#### Respiratory sensitization

Not classified based on available information.

#### Components:

##### Titanium dioxide:

Test Type	: Buehler Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: negative

Routes of exposure	: Inhalation
Species	: Mouse
Result	: negative

Routes of exposure	: Inhalation
Species	: Humans
Result	: negative

##### Laminate component:

Routes of exposure	: Skin contact
Species	: Guinea pig
Result	: negative
Remarks	: Based on data from similar materials

Species	: Mouse
Result	: negative
Remarks	: Based on data from similar materials

##### Aluminium hydroxide:

Test Type	: Maximization Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative

### Germ cell mutagenicity

Not classified based on available information.

#### Components:

##### Titanium dioxide:



# SAFETY DATA SHEET



## Ti-Pure™ R-796+ Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 09/15/2021
4.7	10/18/2022	1560916-00012	Date of first issue: 04/21/2017

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative
- Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative
- Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative
- Test Type: comet assay  
Method: OPPTS 870.5140  
Result: positive
- Genotoxicity in vivo : Test Type: In vivo mammalian alkaline comet assay  
Species: Rat  
Application Route: intratracheal  
Method: OECD Test Guideline 489  
Result: negative
- Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 474  
Result: negative
- Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 475  
Result: negative
- Test Type: Transgenic rodent germ cell gene mutation assay  
Species: Mouse  
Application Route: Intravenous injection  
Method: OECD Test Guideline 488  
Result: negative
- Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.
- Aluminium hydroxide:**
- Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative
- Test Type: Chromosome aberration test in vitro  
Result: positive  
Remarks: Based on data from similar materials

# SAFETY DATA SHEET



## Ti-Pure™ R-796+ Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue:
4.7	10/18/2022	1560916-00012	09/15/2021
			Date of first issue: 04/21/2017

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)  
Result: equivocal  
Remarks: Based on data from similar materials

Test Type: in vitro micronucleus test  
Result: positive  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 474  
Result: negative

### Carcinogenicity

Not classified based on available information.

### Product:

Remarks : In lifetime inhalation studies rats were exposed for 2 years to respectively 10, 50 and 250 mg/m<sup>3</sup> of respirable TiO<sub>2</sub>. Slight lung fibrosis was observed at 50 and 250 mg/m<sup>3</sup> levels. Microscopic lung tumours were also observed in 13 percent of the rats exposed to 250 mg/m<sup>3</sup>, an exposure level that caused lung overloading and impairment of rat lungs clearance mechanisms.

In further studies, these tumours were found to occur only under particle overload conditions in a uniquely sensitive species, the rat, and have little or no relevance for humans. The pulmonary inflammatory response to TiO<sub>2</sub> particles exposure was also found to be much more severe in rats than in other rodent species.

In February 2006, IARC has re-evaluated Titanium dioxide as pertaining to Group 2B: "possibly carcinogenic to humans", based upon inadequate evidence in humans and sufficient evidence in experimental animals for the carcinogenicity of titanium dioxide. IARC evaluation guidelines consider the generation of tumours, in 2 different studies within the same animal species, to be adequate criteria for an assessment of sufficient evidence.

The conclusions of several epidemiology studies on more than 20000 TiO<sub>2</sub> industry workers in Europe and the USA did not suggest a carcinogenic effect of TiO<sub>2</sub> dust on the human lung. Mortality from other chronic diseases, including other respiratory diseases, was also not associated with exposure to TiO<sub>2</sub> dust.

Based upon all available study results, Chemours scientists conclude that titanium dioxide will not cause lung cancer or chronic respiratory diseases in humans at concentrations experienced in the workplace.

# SAFETY DATA SHEET



## Ti-Pure™ R-796+ Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 09/15/2021
4.7	10/18/2022	1560916-00012	Date of first issue: 04/21/2017

### Components:

#### **Titanium dioxide:**

Species	: Rat
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 2 Years
Result	: negative

Species	: Rat
Application Route	: Ingestion
Exposure time	: 105 weeks
Result	: negative

Species	: Mouse
Application Route	: Ingestion
Exposure time	: 103 weeks
Result	: negative

Carcinogenicity - Assessment	: Weight of evidence does not support classification as a carcinogen
------------------------------	--

#### **Laminate component:**

Carcinogenicity - Assessment	: Weight of evidence does not support classification as a carcinogen, Based on data from similar materials
------------------------------	--

#### **Aluminium hydroxide:**

Species	: Rat
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 86 weeks
Result	: negative
Remarks	: Based on data from similar materials

<b>IARC</b>	Group 2B: Possibly carcinogenic to humans	
	Titanium dioxide	13463-67-7

<b>OSHA</b>	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
-------------	--

<b>NTP</b>	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
------------	--

#### **Reproductive toxicity**

Not classified based on available information.

### Components:

#### **Titanium dioxide:**

Effects on fertility	: Test Type: One-generation reproduction toxicity study
	Species: Rat
	Application Route: Ingestion
	Method: OECD Test Guideline 443
	Result: negative

# SAFETY DATA SHEET



## Ti-Pure™ R-796+ Titanium Dioxide Pigment

Version 4.7	Revision Date: 10/18/2022	SDS Number: 1560916-00012	Date of last issue: 09/15/2021 Date of first issue: 04/21/2017
----------------	------------------------------	------------------------------	---

Effects on fetal development : Test Type: Prenatal development toxicity study (teratogenicity)  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 414  
Result: negative

Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity

### Laminate component:

Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity, Based on data from similar materials

### Aluminium hydroxide:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 422  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Result: negative

### STOT-single exposure

Not classified based on available information.

#### Components:

##### Titanium dioxide:

Routes of exposure : Skin contact  
Assessment : No significant health effects observed in animals at concentrations of 2000 mg/kg bw or less

Routes of exposure : Ingestion  
Assessment : No significant health effects observed in animals at concentrations of 2000 mg/kg bw or less

Routes of exposure : inhalation (dust/mist/fume)  
Assessment : No significant health effects observed in animals at concentrations of 5.0 mg/l/4h or less

### STOT-repeated exposure

Not classified based on available information.

#### Components:

##### Titanium dioxide:

Routes of exposure : Ingestion  
Assessment : No significant health effects observed in animals at concentra-

# SAFETY DATA SHEET



## Ti-Pure™ R-796+ Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 09/15/2021
4.7	10/18/2022	1560916-00012	Date of first issue: 04/21/2017

tions of 100 mg/kg bw or less.

Routes of exposure : inhalation (dust/mist/fume)  
Assessment : No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

Routes of exposure : Ingestion  
Assessment : No significant health effects observed in animals at concentrations of 200 mg/kg bw or less.

### Laminate component:

Assessment : No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

### Repeated dose toxicity

#### Components:

##### Titanium dioxide:

Species : Rat, male and female  
NOAEL : 24,000 mg/kg  
LOAEL : > 24,000 mg/kg  
Application Route : Ingestion  
Exposure time : 28 Days  
Method : OECD Test Guideline 407  
Remarks : No significant adverse effects were reported

Species : Rat, male and female  
NOAEL : 0.01 mg/l  
LOAEL : 0.5 mg/l  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 24 Months  
Method : OECD Test Guideline 453  
Remarks : No significant adverse effects were reported

Species : Rat, male and female  
NOAEL : 962 mg/kg  
LOAEL : > 962 mg/kg  
Application Route : Ingestion  
Exposure time : 90 Days  
Method : OECD Test Guideline 408  
Remarks : No significant adverse effects were reported

### Laminate component:

Species : Dog  
NOAEL : 88 mg/kg  
LOAEL : > 88 mg/kg  
Application Route : Ingestion  
Exposure time : 180 d  
Remarks : No significant adverse effects were reported

# SAFETY DATA SHEET



## Ti-Pure™ R-796+ Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 09/15/2021
4.7	10/18/2022	1560916-00012	Date of first issue: 04/21/2017

### Aluminium hydroxide:

Species	: Rat
NOAEL	: > 100 mg/kg
Application Route	: Ingestion
Exposure time	: 364 Days
Method	: OECD Test Guideline 426
Remarks	: Based on data from similar materials

Species	: Rat
NOAEL	: > 0.2 mg/kg
Application Route	: inhalation (dust/mist/fume)
Exposure time	: 12 Months
Remarks	: Based on data from similar materials

### Aspiration toxicity

Not classified based on available information.

### Components:

#### Titanium dioxide:

No aspiration toxicity classification

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

### Components:

#### Titanium dioxide:

Toxicity to fish	: LC50 (Fish): > 1,000 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
	LC50 (Marine species): > 10,000 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia sp. (Water flea)): > 1,000 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
	EC50 (No species specified): > 1,000 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: ErC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
	EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l Exposure time: 72 h Method: ISO 10253

# SAFETY DATA SHEET



## Ti-Pure™ R-796+ Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 09/15/2021
4.7	10/18/2022	1560916-00012	Date of first issue: 04/21/2017

---

NOEC (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l

Exposure time: 3 d

Method: OECD Test Guideline 201

NOEC (Skeletonema costatum (marine diatom)): 5,600 mg/l

Exposure time: 3 d

Method: ISO 10253

### Laminate component:

#### Ecotoxicology Assessment

Acute aquatic toxicity : Toxic effects cannot be excluded

Chronic aquatic toxicity : Toxic effects cannot be excluded

### Aluminium hydroxide:

Toxicity to fish : LL50 (Salmo trutta (brown trout)): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EL50 (Selenastrum capricornutum (green algae)): > 100 mg/l  
Exposure time: 96 h

### Persistence and degradability

#### Components:

#### Laminate component:

Biodegradability : Result: Not readily biodegradable.

### Bioaccumulative potential

#### Components:

#### Titanium dioxide:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)  
Bioconcentration factor (BCF): 352

### Mobility in soil

No data available

### Other adverse effects

No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

# SAFETY DATA SHEET



## Ti-Pure™ R-796+ Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 09/15/2021
4.7	10/18/2022	1560916-00012	Date of first issue: 04/21/2017

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

Not regulated as a dangerous good

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Domestic regulation

##### 49 CFR

Not regulated as a dangerous good

#### Special precautions for user

Not applicable

### SECTION 15. REGULATORY INFORMATION

#### CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : No SARA Hazards

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### US State Regulations

##### Pennsylvania Right To Know

Titanium dioxide  
Laminate component  
Inorganic metal oxide

13463-67-7  
Trade secret  
Trade secret



# SAFETY DATA SHEET



## Ti-Pure™ R-796+ Titanium Dioxide Pigment

Version 4.7      Revision Date: 10/18/2022      SDS Number: 1560916-00012      Date of last issue: 09/15/2021  
Date of first issue: 04/21/2017

### California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which is/are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### California Permissible Exposure Limits for Chemical Contaminants


Titanium dioxide

13463-67-7

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA 704:



#### HMIS® IV:

HEALTH	/	0
FLAMMABILITY		0
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "/" represents a chronic hazard, while the "0" represents the absence of a chronic hazard.

Ti-Pure™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC.

Chemours™ and the Chemours Logo are trademarks of The Chemours Company.

Before use read Chemours safety information.

For further information contact the local Chemours office or nominated distributors.

These products may not be directly added to food, pharmaceuticals, cosmetics, or cigarette papers/filters for tobacco products.

Do not use or resell Chemours™ materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless agreed to by Seller in a written agreement covering such use. For further information, please contact your Chemours representative.

In the manufacture of titanium dioxide, product is packaged at temperatures of approximately 100 to 120°C (212 to 248°F). When pigment is shipped shortly after manufacture, it may stay hot for a very long time depending on ambient temperatures and inventory storage practices. Use caution while handling hot pigment to prevent burns to personnel. Use caution in solvent applications to prevent ignition of solvent.

### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants

# SAFETY DATA SHEET



## Ti-Pure™ R-796+ Titanium Dioxide Pigment

Version	Revision Date:	SDS Number:	Date of last issue: 09/15/2021
4.7	10/18/2022	1560916-00012	Date of first issue: 04/21/2017

ACGIH / TWA : 8-hour, time-weighted average  
OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 10/18/2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8